



USANG

裕程實業有限公司

October 2023

PERSONAL PROTECTIVE EQUIPMENT

Fall Protection Hardware Components
Mountaineering Hardware Components
Racing Harness Hardware Components
Custom OEM/ODM Manufacturing Projects

ISO 9001:2015 / ISO 14001:2015

CE 2777

UK 0321
CA

CSA
c us

HL
89




USANG, established in Taiwan since 1977, has played a major role in manufacturing and exporting of Cargo Control Systems Hardware. Our continuous improvements in product design and quality over the past 44 years have given us an impeccable reputation. Worldwide, we are regarded as a reputed company who offers high quality products and excellent services.

Today, USANG specializes in manufacturing of fall protection hardware, Grade 80/100 overhead lifting hooks, auto racing harness hardware, and mountaineering hardware. We also welcome custom OEM/ODM manufacturing projects. Our accumulated product development and manufacturing experiences over the past years has proved to be valuable assets to our customers.

We have strict quality control at our ISO 9001:2015 certified production plants to ensure high customer satisfaction of our products, and our business philosophy is to provide our customers with the necessary collaboration and support to meet their goals.

USANG products are covered by our Product Liability Insurance policy, written in the amount of 5 million USD



Technical specifications and dimensions presented in this catalog are for reference only. Please confirm all specifications and dimensions with our sales representative before placing an order.

Quality Control, Standards Compliant, and QC Lab Capabilities

We manufacture our products with strict quality control. Our production facilities are ISO 9001:2015 certified, and we operate an in-house QC Lab with capabilities to perform relevant manufacturing test requirements for international standards such as ANSI Z359.12, CSA Z259.12, CE EN362, NFPA 1983 and CE EN1677.

A broad range of our products are certified by 3rd party test laboratories, and committed to certification audit programs. Currently, we have certification audit programs with CSA Group, SATRA Technology Europe, Underwriters Laboratories Inc., and BG PRÜFZERT. At USANG, we are committed to supply 3rd party certified products to our customers, and will continue to broaden our certified products range.





Salt spray tester



Static strength tester



Drop tower



Hardness tester



Spectrum analyzer (XRF)



Coating thickness gauge



Dielectric/Insulation tester



Profile projector



Gate cycle tester



Magnetic particle inspection station



Coordinate-measuring machine (CMM)



Drop impact tester



OE Spectrometer



Surface roughness tester



Portable CMM

SECTION INDEX	PAGE
COMPANY PROFILE	1-7
SNAPHOOKS	8-18
CLEVIS SNAPHOOKS	18-18
SPREADER SNAPHOOKS	18-19
STRAP SNAPHOOKS	19-21
LARGE SNAPHOOKS	21-27
SWIVEL SNAPHOOKS	28-34
SWIVEL CARABINERS	34-37
SWIVELS	37-39
CARABINERS WITH INTEGRAL EYE	40-43
CARABINERS WITH INTEGRAL WEB SLOT	44-44
CARABINERS	44-68
SLINGS	68
LARGE CARABINERS	69-75
QUICK LINKS	75-77
DESCENDERS	78-82
ASCENDERS	82-84
ROPE GRABS	84-89
ANCHORAGE CONNECTORS	90-92
PULLEYS	92-95
O-RINGS	96-98
D-RINGS	98-102
SINGLE SLOT D-RINGS	102-114
DOUBLE SLOT D-RINGS	114-118
BUCKLES	119-149
RACING HARNESS HARDWARES	149-154
PLASTIC COMPONENTS	155-170
ACCESSORIES	170-176

Certification mark**Description**

ANSI Z359.12-2019 certified for industrial use.
CSA Z259.12-2016 certified for industrial use.



CE certified for industrial use. (Connectors)



CE certified for industrial and climbing use. (Connectors)



CE certified for industrial use. (Lanyards)



CE certified for industrial use. (Anchors)



CE certified for climbing use. (Connectors)



CE certified for climbing use. (Pulleys)



CE certified for climbing use. (Rope clamps)



CE certified for climbing use. (Slings)



CE certified for industrial and climbing use. (Rope clamps)



UK Conformity Assessed



UL Classified / NFPA 2500 (2022ED)



UIAA

UIAA certified for climbing use.

Steel products

We recommend yellow zinc plate ("yellow chromate") finish for its good corrosion resistance performance vs. price ratio.

Aluminum products

Our standard anodized finish is in clear color, normally. Other anodized colors are available, but subject to availability, and minimum order quantity. Product photos shown in other colors are for reference only.

Special surface finish requests


Please contact our sales representative for your special surface finish needs.

SNAPHOOKS

(Page 8)


S-2632A FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 217g / 7.7oz




S-2632 FORGED STEEL SNAPHOOK (PATENTED)

Gate mechanism : Triple action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 214g / 7.5oz




S-2625 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 247g / 8.7oz




S-2625A ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 149g / 5.3oz



S-302L STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 212g / 7.5oz




SNAPHOOKS

(Page 9)


S-302 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 238g / 8.4oz




S-302I STAINLESS STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile stainless steel 420J2
Standard finish : Chrome plate
Weight : 230g / 8.1oz




S-2046 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 152g / 5.4oz




S-2379 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 152g / 5.4oz



S-2303 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 211g / 7.4oz




SNAPHOOKS

(Page 10)


S-633 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Chrome plate
 Weight : 281g / 9.9oz




S-2008 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 294g / 10.4oz




S-2250 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 276g / 9.7oz




S-2645 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 173g / 6.1z



S-2089 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 27kN / 6070LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 162g / 5.7oz




SNAPHOOKS

(Page 11)


S-2008-1 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 273g / 9.6oz




S-2008-1 STAINLESS STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile stainless steel 420J2
Standard finish : Chrome plate
Weight : 274g / 9.7oz




S-2049 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 27kN / 6070LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 276g / 9.7oz




S-2152 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 304g / 10.7oz



S-2393 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 282g / 10oz




SNAPHOOKS

(Page 12)


S-999 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 277g / 9.8oz




S-398 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 296g / 10.4oz




S-2653 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 401g / 14.1oz




S-2156 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 249g / 8.8oz



S-2156A FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 249g / 8.8oz




SNAPHOOKS

(Page 13)



S-2090 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 33kN / 7418LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 117g / 4.1oz





S-2090-1 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 33kN / 7418LBS $\blacklozenge$ 10kN $\curvearrowright$ 15kN
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 127g / 4.5oz




S-2090-1A FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS $\blacklozenge$ 8kN $\curvearrowright$ 8kN
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 127g / 4.5oz




S-2090-1K FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 37kN / 8317LBS $\blacklozenge$ 8kN
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 127g / 4.5oz



S-2090-1AK FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 7kN
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 127g / 4.5oz



SNAPHOOKS


(Page 14)

S-2239 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 33kN / 7418LBS $\blacklozenge$ 8kN
Material : Aluminum alloy
Standard finish : Anodized
Weight : 132g / 4.7oz

CE EN362
EN12275

UK
CA




S-2239A FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS $\blacklozenge$ 7kN
Material : Aluminum alloy
Standard finish : Anodized
Weight : 132g / 4.7oz

CE EN362
EN12275


UK
CA



S-2682 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 126g / 4.4oz


CE EN362



S-2682A FORGED ALUMINUM SNAPHOOK


Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 26kN / 5845LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 126g / 4.4oz

CE EN362



S-2940 FORGED ALUMINUM SNAPHOOK NEW!

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 184g / 6.5oz




SNAPHOOKS

(Page 15)


S-2940N FORGED ALUMINUM SNAPHOOK **NEW!**

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 170g / 6.0oz



S-399 FORGED STEEL SNAPHOOK


Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 477g / 16.8oz



S-3638 STEEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016


Gate mechanism : Double action / Self locking
Gate strength : 16kN / 3600LBS
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 351g / 12.4oz



S-3691 FORGED STEEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016


Gate mechanism : Double action / Self locking
Gate strength : 16kN / 3600LBS
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 385g / 13.6oz



S-3639 FORGED STEEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking
Gate strength : 16kN / 3600LBS
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 382g / 13.5oz



SNAPHOOKS

(Page 16)

S-3628 STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 292g / 10.3oz



S-3614 FORGED STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 322g / 10.4oz



S-3631 FORGED ALUMINUM SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 266g / 9.4oz



S-3603 STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 297g / 10.3oz



S-3602 FORGED STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 320g / 10.4oz



SNAPHOOKS

(Page 17)

S-3608 STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 346g / 12.2oz



S-3609 FORGED STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 369g / 13oz



S-3606 STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 352g / 12.4oz



S-3607 FORGED STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 392g / 13.8oz



S-3610 STEEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 293g / 10.4oz



S-3611 FORGED STEEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 289g / 10.2oz



S-3620 FORGED STEEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 357g / 12.6oz



S-3629 FORGED ALUMINUM SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 301g / 10.7oz



S-334 FORGED STEEL SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 271g / 9.6oz



S-2008C FORGED STEEL CLEVIS SNAPHOOK


Gate mechanism : Double action / Self locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 320g / 11.3oz



SPREADER SNAPHOOKS / STRAP SNAPHOOKS

(Page 19)

S-3622 FORGED STEEL CLEVIS SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 389g / 13.7oz



S-2340 STEEL SPREADER SNAPHOOK


Gate mechanism : Double action / Self locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 525g / 18.5oz



S-3623 FORGED STEEL SPREADER SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 726g / 25.6oz



S-3624 STEEL SPREADER SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 669g / 23.6oz



S-2390 FORGED STEEL STRAP SNAPHOOK


Gate mechanism : Double action / Self locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 368g / 13oz




STRAP SNAPHOOKS

(Page 20)


S-970 FORGED STEEL STRAP SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 355g / 12.5oz



S-2383 STEEL STRAP SNAPHOOK


Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 265g / 9.4oz



S-3626 FORGED STEEL STRAP SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016


Gate mechanism : Double action / Self locking
 Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 428g / 15.1oz



S-3627 FORGED STEEL STRAP SNAPHOOK


Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking
 Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 428g / 15.1oz



S-2327 FORGED STEEL STRAP SNAPHOOK

Gate mechanism : Single action / Self closing / Non-Locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 185g / 6.6oz



STRAP SNAPHOOKS / LARGE SNAPHOOKS

(Page 21)

S-23271 FORGED STAINLESS STEEL STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile stainless steel 420J2

Standard finish : Yellow / Silver zinc plate / Silver dacromet

Weight : 185g / 6.6oz



S-2328 FORGED STEEL STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 118g / 4.2oz



S-989 FORGED STEEL STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 160g / 5.7oz



S-2329 FORGED STEEL STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 237g / 8.4oz



S-2229 STEEL SNAPHOOK


Gate mechanism : Double action / Self locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 363g / 12.8oz




LARGE SNAPHOOKS

(Page 22)


S-2830 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 15kN / 3372LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 348g / 12.3oz




S-2093 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 12kN / 2698LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 343g / 12.1oz




S-2727 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 324g / 11.4oz




S-2892 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 239g / 8.4oz



S-2854 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 363g / 12.8oz




LARGE SNAPHOOKS

(Page 23)


S-634 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Chrome plate
 Weight : 514g / 18.1oz




S-2112 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 498g / 17.6oz




S-2001 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 652g / 23oz




S-2230 FORGED STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 577g / 20.4oz



S-2925 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : Aluminum alloy
 Standard finish : Self colored / Anodized
 Weight : 488g / 17.2oz




LARGE SNAPHOOKS

(Page 24)


S-2078W FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 485g / 17.1oz




S-2078M FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 492g / 17.4oz




S-2078 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 482g / 17oz




S-979C FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 475g / 16.8oz



S-979-22 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 468g / 16.5oz




LARGE SNAPHOOKS

(Page 25)



S-979-28 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 28kN / 6295LBS
 Material : Aluminum alloy
 Standard finish : Self colored / Anodized
 Weight : 468g / 16.5oz





S-2500 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : Aluminum alloy
 Standard finish : Self colored / Anodized
 Weight : 474g / 16.7oz




S-2500T FORGED ALUMINUM SNAPHOOK

Gate mechanism : Triple action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : Aluminum alloy
 Standard finish : Self colored / Anodized
 Weight : 503g / 17.7oz



S-2500TAZ FORGED ALUMINUM SNAPHOOK **NEW!**

Gate mechanism : Triple action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : Aluminum alloy
 Standard finish : Self colored / Anodized
 Weight : 618g / 21.8oz




S-979P FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS
 Material : Aluminum alloy
 Standard finish : Self colored / Anodized
 Weight : 490g / 17.3oz
 Not available in South Africa



Attachment ring for
telescopic pole



LARGE SNAPHOOKS

(Page 26)

S-3640 FORGED STEEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 776g / 27.4oz



S-3634 FORGED STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 599g / 21oz



S-3612 STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 707g / 24.9oz



S-3615 FORGED STEEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 775g / 27.3oz



S-3618 FORGED ALUMINUM SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 689g / 24.3oz




LARGE SNAPHOOKS

(Page 27)


S-2613 STEEL SNAPHOOK (PATENTED)

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 779g / 27.5oz




S-2005 STEEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 861g / 30.4oz




S-9981A FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 904g / 31.9oz




S-2084 FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 920g / 32.5oz



S-2084A FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 925g / 32.5oz




S-2084P FORGED ALUMINUM SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Aluminum alloy
Standard finish : Self colored / Anodized
Weight : 1043g / 36.8oz

CE EN362 CE EN795

Attachment ring for
telescopic pole



S-2042 PIPE-FORM ANCHOR HOOKS (3 models)

Gate mechanism : Single action / Self closing / Non-Locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Stainless steel
Standard finish : Self colored


CE EN362

Model	Dimensions (mm)			Weight	
	G	E	L	(g)	(oz)
S-2042-50	90	37	329	294	10.4
S-2042-75	125	37	395	344	12.1
S-2042-100	155	37	426	382	13.5

S-2042-100

S-2042-75

S-2042-50




SWIVEL SNAPHOOKS

(Page 29)

S-2050 FORGED STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 385g / 13.6oz




S-2050L FORGED STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 389g / 13.7oz




WITH LOAD
INDICATOR




S-2050I FORGED STAINLESS STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile stainless steel 420J2
Standard finish : Chrome plate
Weight : 381g / 13.4oz




S-2050IL FORGED STAINLESS STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile stainless steel 420J2
Standard finish : Chrome plate
Weight : 394g / 13.9oz





WITH LOAD
INDICATOR



S-2146A FORGED STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 356g / 12.6oz




SWIVEL SNAPHOOKS


(Page 30)

S-2146 FORGED STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 356g / 12.6oz




LOAD INDICATOR ACTIVATED
WITH LOAD INDICATOR




S-2043 FORGED STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 381g / 13.4oz




S-839 FORGED STEEL SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 27kN / 6070LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Nickle plate
Weight : 356g / 12.6oz



S-2335A FORGED ALUMINUM SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 183g / 6.5oz




S-2335AL FORGED ALUMINUM SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 183g / 6.5oz



LOAD INDICATOR ACTIVATED
WITH LOAD INDICATOR



SWIVEL SNAPHOOKS

(Page 31)

S-3642 FORGED STEEL SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 501g / 17.7oz



S-3642L FORGED STEEL SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 488g / 17.2oz



WITH LOAD
INDICATOR



S-3605 FORGED STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 450g / 15.9oz



S-3605L FORGED STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 442g / 15.6oz



WITH LOAD
INDICATOR



S-3621 FORGED STEEL SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 479g / 16.9oz



SWIVEL SNAPHOOKS

(Page 32)

S-3621L FORGED STEEL SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 464g / 16.4oz



WITH LOAD INDICATOR



S-3621I FORGED STAINLESS STEEL SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile stainless steel 630 / 17-4PH

Standard finish : Self colored

Weight : 495g / 17.5oz



S-3621IL FORGED STAINLESS STEEL SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS


Material : High tensile stainless steel 630 / 17-4PH

Standard finish : Self colored

Weight : 488g / 17.2oz



WITH LOAD INDICATOR



S-3619 FORGED STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 504g / 17.8oz



S-3619L FORGED STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 498g / 17.6oz



WITH LOAD INDICATOR



SWIVEL SNAPHOOKS

(Page 33)

S-3617 FORGED STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 508g / 17.9oz



S-3617L FORGED STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 499g / 17.6oz



S-3625 FORGED ALUMINUM SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 345g / 12.2oz



S-3625L FORGED ALUMINUM SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 346g / 12.2oz



S-2926 FORGED ALUMINUM SWIVEL SNAPHOOK


Gate mechanism : Double action / Self locking

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 550g / 19.4oz




SWIVEL SNAPHOOKS

(Page 34)


S-2926L FORGED ALUMINUM SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 547g / 19.3oz




S-2710 FORGED ALUMINUM SWIVEL SNAPHOOK

Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 513g / 18.1oz



S-2710L FORGED ALUMINUM SWIVEL SNAPHOOK


Gate mechanism : Double action / Self locking
 Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 511g / 18.0oz



S-3616 STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016


Gate mechanism : Double action / Self locking
 Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 880g / 31oz



S-3616L STEEL SWIVEL SNAPHOOK (PATENTED)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking
 Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 877g / 30.9oz



SWIVEL SNAPHOOKS

(Page 35)

S-3651 FORGED ALUMINUM SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking

Gate strength : 16kN / 3600LBS


Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 700g / 24.7oz

Pending certification to : EN362, ANSI Z359.12, CSA Z259.12



S-3651L FORGED ALUMINUM SWIVEL SNAPHOOK

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Double action / Self locking

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : Aluminum alloy


Standard finish : Anodized

Weight : 703g / 24.8oz

Pending certification to : EN362, ANSI Z359.12, CSA Z259.12



WITH LOAD INDICATOR



S-2086 FORGED STEEL SWIVEL CARABINER


Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 336g / 11.9oz



S-2679 FORGED STEEL SWIVEL CARABINERS (6 models)

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Load indicator	Weight (g) (oz)
S-2679S	Screw lock / Manual locking		327 11.5
S-2679SL	Screw lock / Manual locking	•	321 11.3
S-2679	Twist lock / Self locking		354 12.4
S-2679L	Twist lock / Self locking	•	345 12.1
S-2679T	Triple lock / Self locking		349 12.3
S-2679TL	Triple lock / Self locking	•	342 12.0


* S-2679SL, S-2679, S-2679T, S-2679TL not shown

S-2679S

S-2679L



WITH LOAD INDICATOR



S50-2679 FORGED STEEL SWIVEL CARABINERS (4 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate




Model	Gate mechanism	Load indicator	Weight (g) (oz)	UK CA
S50-2679	Twist lock / Self locking		370 13.0	
S50-2679L	Twist lock / Self locking	•	365 12.8	•
S50-2679T	Triple lock / Self locking		368 12.9	
S50-2679TL	Triple lock / Self locking	•	363 12.8	•

* S50-2679, S50-2679L, S50-2679T not shown



WITH LOAD INDICATOR



S50-2679TL

SWIVEL SNAPHOOKS / SWIVEL CARABINERS

(Page 36)

S-2150 FORGED STEEL SWIVEL CARABINERS (4 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

CE EN362

Model	Gate mechanism	Load indicator	Weight	
			(g)	(oz)
S-2150	Twist lock / Self locking		371	13.1
S-2150L	Twist lock / Self locking	•	370	13.1
S-2150T	Triple lock / Self locking		369	13
S-2150TL	Triple lock / Self locking	•	368	13

* S-2150L, S-2150T not shown




S-2150



WITH LOAD INDICATOR



S-2150TL



S-2150I FORGED STAINLESS STEEL SWIVEL CARABINERS (4 models)

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

CE EN362 UK CA

Model	Gate mechanism	Load indicator	Weight	
			(g)	(oz)
S-2150I	Twist lock / Self locking		368	13
S-2150IL	Twist lock / Self locking	•	367	13
S-2150IT	Triple lock / Self locking		366	13
S-2150ITL	Triple lock / Self locking	•	365	13

* S-2150IL, S-2150IT not shown


S-2150I



WITH LOAD INDICATOR



S-2150ITL



S50-2150 FORGED STEEL SWIVEL CARABINERS (4 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 22kN / 5000LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

CE EN362 UK CA ANSI Z359.12 CSA Z259.12

Model	Gate mechanism	Load indicator	Weight		Certifications	
			(g)	(oz)	CE EN362	ANSI Z359.12 CSA Z259.12
S50-2150	Twist lock / Self locking		392	13.8	•	•
S50-2150L	Twist lock / Self locking	•	391	13.8	•	•
S50-2150T	Triple lock / Self locking		390	13.8	•	•
S50-2150TL	Triple lock / Self locking	•	389	13.7	•	•


* S50-2150, S50-2150L, S50-2150T not shown



WITH LOAD INDICATOR



S50-2150TL



S50-2150I FORGED STAINLESS STEEL SWIVEL CARABINERS (4 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile stainless steel 630 / 17-4PH

Standard finish : Self colored

CE EN362 UK CA ANSI Z359.12 CSA Z259.12

Model	Gate mechanism	Load indicator	Weight	
			(g)	(oz)
S50-2150I	Twist lock / Self locking		402	14.2
S50-2150IL	Twist lock / Self locking	•	396	14
S50-2150IT	Triple lock / Self locking		398	14
S50-2150ITL	Triple lock / Self locking	•	389	13.7


* S50-2150I, S50-2150IL, S50-2150IT not shown



WITH LOAD INDICATOR



S50-2150ITL



SWIVEL CARABINERS

(Page 37)

S-2150A FORGED ALUMINUM SWIVEL CARABINERS (6 models)

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Anodized

CE EN362

UK CA



Model	Gate mechanism	Load indicator	Weight		UK CA
			(g)	(oz)	
S-2150AS	Screw lock / Manual locking		161	5.7	
S-2150ASL	Screw lock / Manual locking	•	156	5.5	
S-2150A	Twist lock / Self locking		170	6	•
S-2150AL	Twist lock / Self locking	•	165	5.8	•
S-2150AT	Triple lock / Self locking		170	6	•
S-2150ATL	Triple lock / Self locking	•	165	5.8	•

* S-2150ASL, S-2150AT, S-2150ATL not shown


S-2150AS

S-2150A



WITH LOAD INDICATOR

S-2150AL



S-3669 FORGED ALUMINUM SWIVEL CARABINERS (4 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : Aluminum alloy

Standard finish : Anodized

CE EN362

UK CA

ANSI Z359.12
CSA Z259.12




Model	Gate mechanism	Load indicator	Weight	
			(g)	(oz)
S-3669	Twist lock / Self locking		211	7.4
S-3669L	Twist lock / Self locking	•	206	7.3
S-3669T	Triple lock / Self locking		211	7.4
S-3669TL	Triple lock / Self locking	•	206	7.3

* S-3669L, S-3669T, S-3669TL not shown



WITH LOAD INDICATOR

S-3669



S-2150C FORGED STEEL SWIVEL CARABINERS (2 models)

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate


CE EN362

UK CA

Model	Gate mechanism	Weight	
		(g)	(oz)
S-2150C	Twist lock / Self locking	359	12.7
S-2150CT	Triple lock / Self locking	353	12.5

S-2150C

S-2150CT



S-2150CI FORGED STAINLESS STEEL SWIVEL CARABINERS (2 models)

Minimum breaking strength : $\blacklozenge$ 28kN / 6294LBS

Material : High tensile stainless steel 630 / 17-4PH

Standard finish : Self colored


CE EN362

UK CA

Model	Gate mechanism	Weight	
		(g)	(oz)
S-2150CI	Twist lock / Self locking	360	12.7
S-2150CIT	Triple lock / Self locking	363	12.8


S-2150CI

S-2150CIT





(Page 38)

Gate mechanism : Express lock / Self locking
Minimum breaking strength : ⚡ 20kN / 4496LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 284g / 10.0oz




Attachment examples



* S-2126, S-2126B, S-2126H not shown

Model	With ball bearing	Weight	
		(g)	(oz)
S-2333		82	2.9
S-2333B	●	91	3.2

* S-2333 not shown



SWIVELS

(Page 39)


S-2126-1 FORGED STEEL EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 171g / 6.1oz




S-2126-1L FORGED STEEL EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile steel

Standard finish : Silver dacromet

Weight : 176g / 6.2oz




S-2126-1I FORGED STAINLESS STEEL EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile stainless steel 630 / 17-4PH

Standard finish : Self colored

Weight : 171g / 6.1oz




S-2358 STAINLESS STEEL EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 17.8kN / 4000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 86g / 3.1oz




S-2701 STAINLESS STEEL EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 17.8kN / 4000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 95g / 3.3oz



SWIVELS

(Page 40)


S-2893 STAINLESS STEEL EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 98g / 3.5oz




S-2863 ALUMINUM EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 5kN / 1124LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 17g / 0.6oz




S-2877 ALUMINUM EYE TO EYE SWIVEL

Minimum breaking strength : $\blacklozenge$ 5kN / 1124LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 16g / 0.6oz




CARABINERS WITH INTEGRAL EYE

(Page 41)

S-2451 STEEL CARABINER WITH INTEGRAL EYE

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 153g / 5.4oz




S-2619 STEEL CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate

Model	Gate mechanism	Weight	
		(g)	(oz)
S-2619S	Screw lock / Manual locking	192	6.8
S-2619	Twist lock / Self locking	222	7.8
S-2619T	Triple lock / Self locking	222	7.8

* S-2619S, S-2619T not shown



S-2149O FORGED STEEL CARABINERS WITH INTEGRAL EYE (2 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2149O	Twist lock / Self locking	286	10.1
S-2149OT	Triple lock / Self locking	286	10.1


* S-2149O not shown



S-2149O




S-2149OT



S-2149 FORGED STEEL CARABINERS WITH INTEGRAL EYE (2 models)

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate




Model	Gate mechanism	Weight	
		(g)	(oz)
S-2149	Twist lock / Self locking	277	9.8
S-2149T	Triple lock / Self locking	275	9.7

* S-2149T not shown




S-2149



S50-2802 FORGED STEEL CARABINER WITH INTEGRAL EYE

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Twist lock / Self locking
 Gate strength : 22kN / 5000LBS
 Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 354g / 12.5oz



CARABINERS WITH INTEGRAL EYE

(Page 42)

S50-2149 FORGED STEEL CARABINERS WITH INTEGRAL EYE (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 22kN / 5000LBS

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2149	Twist lock / Self locking	283	10
S50-2149T	Triple lock / Self locking	281	9.9

* S50-2149T not shown



S-2437K FORGED STEEL CARABINERS WITH INTEGRAL EYE (3 models)


Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2437KS	Screw lock / Manual locking	237	8.4
S-2437K	Twist lock / Self locking	261	9.2
S-2437KT	Triple lock / Self locking	262	9.2



S50-2437K FORGED STEEL CARABINERS WITH INTEGRAL EYE (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS


Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2437K	Twist lock / Self locking	281	9.9
S50-2437KT	Triple lock / Self locking	277	9.8



S-2149K FORGED STEEL CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2149KS	Screw lock / Manual locking	273	9.6
S-2149K	Twist lock / Self locking	292	10.3
S-2149KT	Triple lock / Self locking	291	10.3

* S-2149K not shown



S50-2149K FORGED STEEL CARABINERS WITH INTEGRAL EYE (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 22kN / 5000LBS


Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2149K	Twist lock / Self locking	311	11
S50-2149KT	Triple lock / Self locking	314	11



S50-2149K

S50-2149KT

CARABINERS WITH INTEGRAL EYE

(Page 43)

S-2149A FORGED ALUMINUM CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 28kN / 6295LBS

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2149AS	Screw lock / Manual locking	100	3.6
S-2149A	Twist lock / Self locking	109	3.9
S-2149AT	Triple lock / Self locking	109	3.9


* S-2149AT not shown



S-2149AS



S-2149A



S36-2370 FORGED ALUMINUM CARABINERS WITH INTEGRAL EYE (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Anodized




Model	Gate mechanism	Dimension (mm)	Weight		UK CA
		G	(g)	(oz)	
S36-2370	Twist lock / Self locking	19	159	5.6	•
S36-2370T	Triple lock / Self locking	18	163	5.7	

* S36-2370T not shown



S36-2370



S36-2370K FORGED ALUMINUM CARABINERS WITH INTEGRAL EYE (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 27kN / 6070LBS

Material : Aluminum alloy

Standard finish : Anodized




Model	Gate mechanism	Weight	
		(g)	(oz)
S36-2370K	Twist lock / Self locking	166	5.9
S36-2370KT	Triple lock / Self locking	166	5.9

* S36-2370K not shown



S36-2370KT



S-2364 STEEL CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2364S	Screw lock / Manual locking	237	8.4
S-2364	Twist lock / Self locking	257	9.1
S-2364T	Triple lock / Self locking	257	9.1


* S-2364T not shown



S-2364S



S-2364



S50-2364 STEEL CARABINERS WITH INTEGRAL EYE (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2364	Twist lock / Self locking	287	10.1
S50-2364T	Triple lock / Self locking	286	10.1



S50-2364



S50-2364T



CARABINERS WITH INTEGRAL EYE

(Page 44)

S-2364I STAINLESS STEEL CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored




Model	Gate mechanism	Weight	
		(g)	(oz)
S-2364IS	Screw lock / Manual locking	237	8.4
S-2364I	Twist lock / Self locking	257	9.1
S-2364IT	Triple lock / Self locking	257	9.1

* S-2364IS, S-2364IT not shown



S-2364I



S-2364A ALUMINUM CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2364AS	Screw lock / Manual locking	87	3.1
S-2364A	Twist lock / Self locking	94	3.3
S-2364AT	Triple lock / Self locking	95	3.4


* S-2364AT not shown



S-2364AS



S-2364A



S-630 FORGED ALUMINUM CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Model	Gate mechanism	Dimensions (mm)		Weight	
		G	L	(g)	(oz)
S-630	Screw lock / Manual locking	17	136	188	6.6
S-630A	Straight gate / Self closing / Non-Locking	17	136	180	6.3
S-630L	Screw lock / Manual locking	20	135	169	6.0




S-630L



S-630



S-630A



S-2723 FORGED ALUMINUM CARABINERS WITH INTEGRAL EYE (3 models)

Minimum breaking strength : $\blacklozenge$ 27kN / 6070LBS

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2723S	Screw lock / Manual locking	241	8.5
S-2723	Twist lock / Self locking	250	8.8
S-2723T	Triple lock / Self locking	252	8.9




S-2723S



S-2723



S-2723T



S-2083 FORGED ALUMINUM CARABINERS WITH INTEGRAL EYE (2 models)

Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized


Model	Gate mechanism	Weight	
		(g)	(oz)
S-2083	Screw lock / Manual locking	236	8.3
S-2083A	Straight gate / Self closing / Non-Locking	228	8



S-2083



S-2083A




CARABINERS WITH INTEGRAL WEB SLOT / CARABINERS

(Page 45)

S-2450 STEEL CARABINER WITH INTEGRAL WEB SLOT

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 131g / 4.6oz




S-2700 STEEL CARABINERS WITH INTEGRAL WEB SLOT (4 models)

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 138g / 4.8oz




Model	Gate mechanism	Weight		CE EN362
(g)	(oz)			
S-2700S	Screw lock / Manual locking	138	4.8	•
S-2700	Twist lock / Self locking	138	4.8	•
S-2700T	Triple lock / Self locking	138	4.8	•
S-2700BS	Straight gate / Self closing / Non-Locking	138	4.8	

* S-2700, S-2700T not shown





S-2801 "OVAL" STEEL CARABINER

Gate mechanism: Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 153g / 5.4oz



S-507 "OVAL" STEEL CARABINERS (4 models)

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Optional captive pin available



S-507



S-507-1



S-507-1T



S-507-1BS

Model	Gate mechanism	$\blacklozenge$		$\blacklozenge$	∞	Weight		Certifications			
		(kN)	(lbs)			(g)	(oz)	CE EN362	CE EN12275	UIAA	UK CA
S-507	Screw lock / Manual locking	25	5620	9kN	8kN	165	5.8	•	•	•	•
S-507-1	Twist lock / Self locking	25	5620	9kN		198	7	•			•
S-507-1T	Triple lock / Self locking	25	5620	9kN		196	6.9	•			•
S-507-1BS	Straight gate / Self closing / Non-Locking	25	5620	9kN	8kN	162	5.7				

CARABINERS

(Page 46)

S50-507-1 "OVAL" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate


Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-507-1	Twist lock / Self locking	215	7.6
S50-507-1T	Triple lock / Self locking	213	7.5

* S50-507-1T not shown

S50-507-1



S-962AS "OVAL" ALUMINUM CARABINER



Gate mechanism: Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS $\blacklozenge$ 8kN $\curvearrowright$ 6kN

Material : Aluminum alloy

Standard finish : Anodized

Weight : 78g / 2.8oz




S-507-1K "OVAL" STEEL CARABINERS (4 models)

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 16kN $\curvearrowright$ 8kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-507-1KS	Screw lock / Manual locking	179	6.3
S-507-1K	Twist lock / Self locking	197	6.9
S-507-1KT	Triple lock / Self locking	198	7
S-507-1KBS	Straight gate / Self closing / Non-Locking	161	5.7

* S-507-1KBS is without EN362 certification



S-507-1KS



S-507-1K



S-507-1KT



S-507-1KBS

S50-507-1K "OVAL" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 16kN $\curvearrowright$ 8kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-507-1K	Twist lock / Self locking	247	8.7
S50-507-1KT	Triple lock / Self locking	251	8.9



S50-507-1K



S50-507-1KT



CARABINERS


(Page 47)

S-2711O "OVAL" STEEL CARABINERS (3 models)


Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 11kN $\curvearrowright$ 14kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2711OS	Screw lock / Manual locking	174	6.1
S-2711O	Twist lock / Self locking	193	6.8
S-2711OT	Triple lock / Self locking	193	6.8




S-2711OS



S-2711OT



S-2711O



S-2633I "OVAL" STAINLESS STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS $\blacklozenge$ 7kN $\curvearrowright$ 7kN

Material : Stainless steel 316

Standard finish : Self colored

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2633IS	Screw lock / Manual locking	242	8.5
S-2633I	Twist lock / Self locking	260	9.2
S-2633IT	Triple lock / Self locking	259	9.1


* S-2633I not shown



S-2633IS



S-2633IT



S-2745 FORGED "OVAL" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : Aluminum alloy

Standard finish : Anodized

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2745S	Screw lock / Manual locking	20	78	2.8
S-2745	Twist lock / Self locking	20	83	2.9
S-2745T	Triple lock / Self locking	19	82	2.9


* S-2745T not shown



S-2745S




S-2745



S-2249A FORGED "OVAL" ALUMINUM CARABINERS (4 models)

Material : Aluminum alloy

Standard finish : Anodized



S-2249AS



S-2249A



S-2249AT



S-2249ABS

Model	Gate mechanism	$\blacklozenge$		$\blacklozenge$	$\curvearrowright$	Dimension (mm)	Weight	
		(kN)	(lbs)			G	(g)	(oz)
S-2249AS	Screw lock / Manual locking	24	5395	10kN	7kN	19	76	2.7
S-2249A	Twist lock / Self locking	24	5395	8kN		19	86	3
S-2249AT	Triple lock / Self locking	24	5395	8kN		19	86	3
S-2249ABS	Straight gate / Self closing / Non-Locking	24	5395	10kN	7kN	22	71	2.5



* S-2249ABS is without EN362 certification

CARABINERS

(Page 48)

S-2345A "OVAL" ALUMINUM CARABINERS (4 models)

Material : Aluminum alloy
Standard finish : Anodized



S-2345AS

S-2345A

S-2345AT


S-2345ABS

Model	Gate mechanism	↕		↕	↪	Dimension (mm)		Weight	
		(kN)	(lbs)			G		(g)	(oz)
S-2345AS	Screw lock / Manual locking	22	5000	7kN	7kN	19		75	2.6
S-2345A	Twist lock / Self locking	22	5000	7kN		19		82	2.9
S-2345AT	Triple lock / Self locking	22	5000	7kN		19		82	2.9
S-2345ABS	Straight gate / Self closing / Non-Locking	22	5000	7kN	7kN	22		67	2.4

* S-2345ABS is without EN362 certification

S-2647A FORGED "OVAL" ALUMINUM CARABINERS (4 models)

Material : Aluminum alloy
Standard finish : Anodized



S-2647AS

S-2647A

S-2647AT


S-2647ABS

Model	Gate mechanism	↕		↕	↪	Dimension (mm)		Weight	
		(kN)	(lbs)			G		(g)	(oz)
S-2647AS	Screw lock / Manual locking	22	5000	8kN	7kN	20		79	2.8
S-2647A	Twist lock / Self locking	22	5000	8kN	7kN	20		86	3.0
S-2647AT	Triple lock / Self locking	22	5000	8kN	7kN	20		86	3.0
S-2647ABS	Straight gate / Self closing / Non-Locking	22	5000	8kN	7kN	22		73	2.6

* S-2647ABS is without EN362 certification

S-2238AWS FORGED "MODIFIED-D" ALUMINUM CARABINER

Gate mechanism: Straight wire / Self closing / Non-Locking
Minimum breaking strength : ↕ 20kN / 4496LBS ↕ 8kN ↪ 8kN
Material : Aluminum alloy
Standard finish : Anodized
Weight : 31g / 1.1oz



S-956A "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : ↕ 27kN / 6070LBS ↕ 7kN ↪ 7kN
Material : Aluminum alloy
Standard finish : Anodized

Model	Gate mechanism	Dimension (mm)		Weight	
		G		(g)	(oz)
S-956AS	Screw lock / Manual locking	15		70	2.5
S-956AWS	Straight wire / Self closing / Non-Locking	26		54	1.9
S-956AWB	Bent wire / Self closing / Non-Locking	28		55	1.9


* S-956AWB not shown



S-956AS



S-956AWS



CARABINERS

(Page 49)


S-2315A FORGED "MODIFIED-D" ALUMINUM CARABINERS (2 models)

Minimum breaking strength : $\blacklozenge$ 24kN / 5395LBS $\blacklozenge$ 7kN $\curvearrowright$ 8kN

Material : Aluminum alloy

Standard finish : Anodized

Weight : 35g / 1.2oz




Model	Gate mechanism
S-2315AWS	Straight wire / Self closing / Non-Locking
S-2315AWB	Bent wire / Self closing / Non-Locking



S-2315AWS



S-2315AWB



S-2910 FORGED "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS $\blacklozenge$ 7kN $\curvearrowright$ 7kN

Material : Aluminum alloy

Standard finish : Anodized




Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2910S	Screw lock / Manual locking	15	50	1.8
S-2910	Twist lock / Self locking	15	50	1.8
S-2910T	Triple lock / Self locking	14	50	1.8

* S-2910S, S-2910T not shown



S-2910



S-2247BB FORGED "MODIFIED-D" STEEL CARABINER


Gate mechanism: Bent gate / Self closing / Non-Locking

Minimum breaking strength : $\blacklozenge$ 32kN / 6744LBS $\blacklozenge$ 13kN $\curvearrowright$ 20kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 104g / 3.7oz



S-2247A FORGED "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 24kN / 5395LBS $\blacklozenge$ 7kN $\curvearrowright$ 9kN

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2247AS	Screw lock / Manual locking	16	50	1.8
S-2247ABS	Straight gate / Self closing / Non-Locking	18	43	1.5
S-2247ABB	Bent gate / Self closing / Non-Locking	22	44	1.6

* S-2247ABS, S-2247ABB are without EN362 certification




S-2247AS



S-2247ABS



S-2247ABB




S-2203A FORGED "MODIFIED-D" ALUMINUM CARABINERS (2 models)

Minimum breaking strength : $\blacklozenge$ 26kN / 5845LBS $\blacklozenge$ 8kN $\curvearrowright$ 10kN

Material : Aluminum alloy

Standard finish : Anodized

Weight : 45g / 1.6oz




Model	Gate mechanism
S-2203AWS	Straight wire / Self closing / Non-Locking
S-2203AWB	Bent wire / Self closing / Non-Locking



S-2203AWS



S-2203AWB



CARABINERS

(Page 50)

S-2109 "MODIFIED-D" STEEL CARABINERS (2 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS $\blacklozenge$ 12kN $\curvearrowright$ 16kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 126g / 4.4oz


Optional captive pin available



Model	Gate mechanism	Dimension (mm)	
		G	
S-2109WS	Straight wire / Self closing / Non-Locking	28	
S-2109WB	Bent wire / Self closing / Non-Locking	30	

S-2109WS

S-2109WB



S-2109KBB "MODIFIED-D" STEEL CARABINER

Gate mechanism: Bent gate / Self closing / Non-Locking



Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 10kN $\curvearrowright$ 12kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 128g / 4.5oz

Optional captive pin available




S-2109A "MODIFIED-D" ALUMINUM CARABINERS (5 models)

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS $\blacklozenge$ 7kN $\curvearrowright$ 7kN


Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Dimension (mm)		Weight	
		G	(g)	(oz)	
S-2109AS	Screw lock / Manual locking	18	63	2.2	
S-2109AWS	Straight wire / Self closing	28	47	1.7	
S-2109AWB	Bent wire / Self closing	30	47	1.7	
S-2109ABS	Straight gate / Self closing	22	56	2	
S-2109ABB	Bent gate / Self closing	23	56	2	

* S-2109AWS, S-2109AWB, S-2109ABS, S-2109ABB are without EN362 certification




S-2300A FORGED "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 26kN / 5845LBS $\blacklozenge$ 8kN $\curvearrowright$ 9kN

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Dimension (mm)		Weight	
		G	(g)	(oz)	
S-2300AS	Screw lock / Manual locking	17	58	2	
S-2300ABS	Straight gate / Self closing / Non-Locking	21	51	1.8	
S-2300ABB	Bent gate / Self closing / Non-Locking	25	51	1.8	

* S-2300ABS, S-2300ABB are without EN362 certification



CARABINERS

(Page 51)

S-2389A ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS $\blacktriangle$ 20kN $\blacklozenge$ 13kN $\curvearrowright$ 7kN

Material : Aluminum alloy

Standard finish : Anodized




Model	Gate mechanism	Weight	
		(g)	(oz)
S-2389AS	Screw lock / Manual locking	93	3.3
S-2389A	Twist lock / Self locking	97	3.4
S-2389AT	Triple lock / Self locking	98	3.5



S-2389AS

S-2389A

S-2389AT




S-2011 "EQUAL-D" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS $\blacklozenge$ 13kN $\curvearrowright$ 13kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Dimension (mm)	Weight		Certifications		
		G	(g)	(oz)	CE EN362	CE EN12275	UIAA
S-2011	Twist lock / Self locking	15	193	6.8	•		
S-2011T	Triple lock / Self locking	15	191	6.7	•		
S-2011S	Screw lock / Manual locking	17	172	6.1	•	•	•

* S-2011T not shown



S-2011S

S-2011



S-2011I "EQUAL-D" STAINLESS STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Optional captive pin available




Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2011IS	Screw lock / Manual locking	17	182	6.4
S-2011I	Twist lock / Self locking	15	198	7
S-2011IT	Triple lock / Self locking	15	197	6.9



S-2011IS

S-2011I

S-2011IT



S50-2011 "EQUAL-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate


Optional captive pin available



Model	Gate mechanism	Weight		Certifications	
		(g)	(oz)	CE EN362	CSA US
S50-2011	Twist lock / Self locking	193	6.8	•	•
S50-2011T	Triple lock / Self locking	191	6.7	•	•

* S50-2011T not shown

S50-2011




CARABINERS

(Page 52)

S-2452 FORGED "EQUAL-D" ALUMINUM CARABINERS (4 models)

Material : Aluminum alloy
Standard finish : Anodized
Optional captive pin available



S-2452S



S-2452



S-2452T



S-2452BS

Model	Gate mechanism	↕		↕	↪	Dimension (mm)		Weight		Certification
		(kN)	(lbs)			G		(g)	(oz)	
S-2452S	Screw lock / Manual locking	28	6295	8kN	8kN	18		75	2.6	
S-2452	Twist lock / Self locking	28	6295	8kN	8kN	18		81	2.9	•
S-2452T	Triple lock / Self locking	28	6295	8kN	8kN	18		81	2.9	•
S-2452BS	Straight gate / Self closing / Non-Locking	28	6295	8kN	8kN	20		68	2.4	

S50-2736I "EQUAL-D" STAINLESS STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : ↕ 30kN / 6744LBS

Material : High tensile stainless steel 630 / 17-4PH

Standard finish : Self colored

Optional captive pin available




Model	Gate mechanism	Dimension (mm)		Weight	
		G		(g)	(oz)
S50-2736I	Twist lock / Self locking	18		304	10.7
S50-2736IT	Triple lock / Self locking	17		304	10.7



S50-2736I



S50-2736IT



S-2011O "EQUAL-D" STEEL CARABINERS (3 models)

Minimum breaking strength : ↕ 40kN / 8992LBS

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2011OS	Screw lock / Manual locking	175	6.2
S-2011O	Twist lock / Self locking	195	6.9
S-2011OT	Triple lock / Self locking	193	6.8


* S-2011OT not shown



S-2011OS



S-2011O



S50-2011O "EQUAL-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016


Gate strength : 16kN / 3600LBS

Minimum breaking strength : ↕ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Weight		Certifications	
		(g)	(oz)	CE EN362	UK CA
S50-2011O	Twist lock / Self locking	214	7.6	•	•
S50-2011OT	Triple lock / Self locking	212	7.5	•	•



S50-2011O



S50-2011OT



CARABINERS

(Page 53)


S-2011K "EQUAL-D" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 13kN



Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2011KS	Screw lock / Manual locking	16	178	6.3
S-2011K	Twist lock / Self locking	15	194	6.8
S-2011KT	Triple lock / Self locking	15	195	6.9



S-2011KS

S-2011K

S-2011KT

S50-2011K "EQUAL-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 13kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2011K	Twist lock / Self locking	216	7.6
S50-2011KT	Triple lock / Self locking	219	7.7



S50-2011K

S50-2011KT

S-2011KO "EQUAL-D" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS $\blacklozenge$ 16kN $\curvearrowright$ 10kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2011KOS	Screw lock / Manual locking	180	6.3
S-2011KO	Twist lock / Self locking	199	7.0
S-2011KOT	Triple lock / Self locking	198	7.0



S-2011KOS

S-2011KO

S-2011KOT

S50-2011KO "EQUAL-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS $\blacklozenge$ 16kN $\curvearrowright$ 10kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2011KO	Twist lock / Self locking	216	7.6
S50-2011KOT	Triple lock / Self locking	219	7.7



S50-2011KO

S50-2011KOT

S-2416 "D-OVAL" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2416S	Screw lock / Manual locking	177	6.2
S-2416	Twist lock / Self locking	197	6.9
S-2416T	Triple lock / Self locking	196	6.9

* S-2416S, S-2416T not shown



S-2416

CARABINERS

(Page 54)


S-2416K "D-OVAL" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 16kN $\curvearrowright$ 10kN



Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2416KS	Screw lock / Manual locking	182	6.4
S-2416K	Twist lock / Self locking	201	7.1
S-2416KT	Triple lock / Self locking	201	7.1



S50-2416K "D-OVAL" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 16kN $\curvearrowright$ 10kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2416K	Twist lock / Self locking	216	7.6
S50-2416KT	Triple lock / Self locking	219	7.7



S-2198K LARGE "EQUAL-D" STEEL CARABINERS (3 models)


Minimum breaking strength : $\blacklozenge$ 65kN / 14612LBS $\blacklozenge$ 16kN $\curvearrowright$ 20kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2198KS	Screw lock / Manual locking	278	9.8
S-2198K	Twist lock / Self locking	295	10.4
S-2198KT	Triple lock / Self locking	297	10.5



S50-2198K LARGE "EQUAL-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS


Minimum breaking strength : $\blacklozenge$ 65kN / 14612LBS $\blacklozenge$ 16kN $\curvearrowright$ 20kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2198K	Twist lock / Self locking	317	11.2
S50-2198KT	Triple lock / Self locking	318	11.2



CARABINERS

(Page 55)

S-2198KO LARGE "EQUAL-D" STEEL CARABINERS (3 models)


Minimum breaking strength : $\blacklozenge$ 60kN / 13489LBS $\blacklozenge$ 16kN $\curvearrowright$ 16kN

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight		Certification
		(g)	(oz)	
S-2198KOS	Screw lock / Manual locking	276	9.7	•
S-2198KO	Twist lock / Self locking	296	10.4	
S-2198KOT	Triple lock / Self locking	300	10.6	



S-2198KOS



S-2198KO



S-2198KOT

S50-2198KO LARGE "EQUAL-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 60kN / 13489LBS $\blacklozenge$ 16kN $\curvearrowright$ 16kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2198KO	Twist lock / Self locking	319	11.3
S50-2198KOT	Triple lock / Self locking	321	11.3



S50-2198KO



S50-2198KOT




S-958 "MODIFIED-D" STEEL CARABINERS (5 models)

Minimum breaking strength : $\blacklozenge$ 41kN / 9217LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



S-958S



S-958




S-958T



S-958WS

Model	Gate mechanism	$\blacklozenge$		$\blacklozenge$	$\curvearrowright$	Weight		Certifications		
		(kN)	(lbs)			(g)	(oz)	CE EN362	CE EN12275	UIAA
S-958S	Screw lock / Manual locking	41	9217	10kN	16kN	208	7.3	•	•	•
S-958	Twist lock / Self locking	41	9217	10kN		231	8.1	•		
S-958T	Triple lock / Self locking	41	9217	10kN		229	8.1	•		
S-958WS	Straight wire / Self closing / Non-Locking	41	9217	7kN	16kN	134	4.7			
S-958WB	Bent wire / Self closing / Non-Locking	41	9217	7kN	16kN	135	4.8			

* S-958WB not shown



S50-958 "MODIFIED-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 41kN / 9217LBS

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-958	Twist lock / Self locking	253	8.9
S50-958T	Triple lock / Self locking	250	8.8

* S50-958T not shown



S50-958

CARABINERS

(Page 56)

S-958K "MODIFIED-D" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS $\blacklozenge$ 16kN $\curvearrowright$ 12kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-958KS	Screw lock / Manual locking	22	215	7.6
S-958K	Twist lock / Self locking	22	234	8.3
S-958KT	Triple lock / Self locking	21	234	8.3



S-958KS



S-958K



S-958KT

S50-958K "MODIFIED-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS $\blacklozenge$ 16kN $\curvearrowright$ 12kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-958K	Twist lock / Self locking	254	9
S50-958KT	Triple lock / Self locking	257	9.1



S50-958K



S50-958KT



S-958IKS "MODIFIED-D" STAINLESS STEEL CARABINER


Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 251g / 8.9oz

Optional captive pin available



S50-958IK "MODIFIED-D" STAINLESS STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : Stainless steel 304

Standard finish : Self colored

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-958IK	Twist lock / Self locking	290	10.2
S50-958IKT	Triple lock / Self locking	290	10.2



S50-958IK



S50-958IKT



S-958I "MODIFIED-D" STAINLESS STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 41kN / 9217LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S-958IS	Screw lock / Manual locking	215	7.6
S-958I	Twist lock / Self locking	233	8.2
S-958IT	Triple lock / Self locking	232	8.2

* S-958IS, S-958I not shown



S-958IT



CARABINERS

(Page 57)

S50-958I "MODIFIED-D" STAINLESS STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 41kN / 9217LBS


Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-958I	Twist lock / Self locking	254	9
S50-958IT	Triple lock / Self locking	253	9



S-958A "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS


Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-958AS	Screw lock / Manual locking	78	2.8
S-958A	Twist lock / Self locking	85	3
S-958AT	Triple lock / Self locking	86	3

* S-958A not shown



S-958AK "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS


Material : Aluminum alloy

Standard finish : Anodized

Optional captive pin available




Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-958AKS	Screw lock / Manual locking	22	88	3.1
S-958AK	Twist lock / Self locking	21	93	3.3
S-958AKT	Triple lock / Self locking	21	97	3.4



S-2002 FORGED "MODIFIED-D" ALUMINUM CARABINERS (4 models)

Material : Aluminum alloy

Standard finish : Anodized



S-2002S

S-2002

S-2002T

S-2002BS

Model	Gate mechanism	$\blacklozenge$		$\blacklozenge$	$\curvearrowright$	Dimension (mm)	Weight		Certifications					
		(kN)	(lbs)			G	(g)	(oz)	CE EN362	CE EN12275	UIAA	UL	UK CA	
S-2002S	Screw lock / Manual locking	28	6295	10kN	8kN	23	78	2.8	•	•	•	•	•	•
S-2002	Twist lock / Self locking	28	6295	8kN	8kN	22	84	3	•	•	•	•	•	•
S-2002T	Triple lock / Self locking	28	6295	8kN	8kN	22	84	3	•	•	•	•	•	•
S-2002BS	Straight gate / Self closing / Non-Locking	28	6295	10kN	8kN	26	73	2.6		•	•			

CARABINERS

(Page 58)

S-2803 FORGED "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Anodized

Optional captive pin available



Model	Gate mechanism	Dimension (mm)		Weight	
		G	(g)	(oz)	
S-2803S	Screw lock / Manual locking	20	76	2.7	
S-2803	Twist lock / Self locking	20	79	2.8	
S-2803T	Triple lock / Self locking	18	79	2.8	




S-2803S



S-2803



S-2803T



S-2629A "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 9kN $\curvearrowright$ 11kN

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Dimension (mm)		Weight	
		G	(g)	(oz)	
S-2629AS	Screw lock / Manual locking	18	75	2.6	
S-2629A	Twist lock / Self locking	17	82	2.9	
S-2629AT	Triple lock / Self locking	17	83	2.9	




S-2629AS



S-2629A



S-2629AT



S-2107 "MODIFIED-D" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)		Weight	
		G	(g)	(oz)	
S-2107S	Screw lock / Manual locking	25	251	8.9	
S-2107	Twist lock / Self locking	24	267	9.4	
S-2107T	Triple lock / Self locking	24	265	9.3	

* S-2107S CE certified model reference is S-2068


* S-2107T not shown



S-2107S



S-2107



S50-2107 "MODIFIED-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight		Certifications
		(g)	(oz)	
S50-2107	Twist lock / Self locking	286	10.1	•
S50-2107T	Triple lock / Self locking	283	10	

* S50-2107T not shown



S50-2107

CARABINERS

(Page 59)


S-2107K "MODIFIED-D" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 52kN / 11690LBS $\blacklozenge$ 16kN $\curvearrowright$ 18kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2107KS	Screw lock / Manual locking	25	251	8.9
S-2107K	Twist lock / Self locking	24	270	9.5
S-2107KT	Triple lock / Self locking	24	270	9.5



S-2107KS



S-2107K



S-2107KT

S50-2107K "MODIFIED-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 52kN / 11690LBS $\blacklozenge$ 16kN $\curvearrowright$ 18kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2107K	Twist lock / Self locking	287	10.1
S50-2107KT	Triple lock / Self locking	289	10.2



S50-2107K



S50-2107KT



S50-2107IK "MODIFIED-D" STAINLESS STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 52kN / 11690LBS $\blacklozenge$ 16kN $\curvearrowright$ 18kN

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2107IK	Twist lock / Self locking	287	10.1
S50-2107IKT	Triple lock / Self locking	289	10.2

* S50-2107IKT not shown



S50-2107IK



S-2107A "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 26kN / 5845LBS $\blacklozenge$ 8kN $\curvearrowright$ 8kN

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Weight		UK CA
		(g)	(oz)	
S-2107AS	Screw lock / Manual locking	92	3.2	•
S-2107A	Twist lock / Self locking	100	3.5	•
S-2107AT	Triple lock / Self locking	98	3.5	•


* S-2107AT not shown



S-2107AS



S-2107A



S-2107AK "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 24kN / 5395LBS $\blacklozenge$ 8kN $\curvearrowright$ 7kN

Material : Aluminum alloy

Standard finish : Anodized

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2107AKS	Screw lock / Manual locking	90	3.2
S-2107AK	Twist lock / Self locking	95	3.4
S-2107AKT	Triple lock / Self locking	96	3.4


* S-2107AK not shown



S-2107AKS



S-2107AKT



CARABINERS

(Page 60)

S-2310 "MODIFIED-D" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 53kN / 11914LBS $\blacklozenge$ 16kN $\curvearrowright$ 18kN

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)		Weight		Certification
		G		(g)	(oz)	
S-2310S	Screw lock / Manual locking	27		261	9.2	•
S-2310	Twist lock / Self locking	27		280	9.9	
S-2310T	Triple lock / Self locking	26		279	9.8	

* S-2310T not shown



S50-2310 "MODIFIED-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 53kN / 11914LBS $\blacklozenge$ 16kN $\curvearrowright$ 18kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)		Weight	
		G		(g)	(oz)
S50-2310	Twist lock / Self locking	23		333	11.7
S50-2310T	Triple lock / Self locking	22		338	11.9




S-2310I6 "MODIFIED-D" STAINLESS STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 35kN / 7868LBS $\blacklozenge$ 11kN $\curvearrowright$ 7kN

Material : Stainless steel 316


Standard finish : Self colored

Optional captive pin available



Model	Gate mechanism	Dimension (mm)		Weight	
		G		(g)	(oz)
S-2310I6S	Screw lock / Manual locking	29		266	9.4
S-2310I6	Twist lock / Self locking	28		287	10.1
S-2310I6T	Triple lock / Self locking	28		285	10.1

* S-2310I6 not shown



S50-2310I "MODIFIED-D" STAINLESS STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS

Material : High tensile stainless steel 420J2


Standard finish : Chrome plate

Optional captive pin available



Model	Gate mechanism	Weight		Certifications
		(g)	(oz)	
S50-2310I	Twist lock / Self locking	296	10.5	
S50-2310IT	Triple lock / Self locking	298	10.5	•

* S50-2310I not shown





CARABINERS

(Page 61)

S-2310A "MODIFIED-D" ALUMINUM CARABINERS (4 models)

Material : Aluminum alloy
Standard finish : Anodized




Model	Gate mechanism	↕		↕	↻	Dimension (mm)		Weight
		(kN)	(lbs)			G	(g)	
S-2310AS	Screw lock / Manual locking	25	5620	10kN	8kN	27	93	3.3
S-2310A	Twist lock / Self locking	25	5620	8kN		27	100	3.5
S-2310AT	Triple lock / Self locking	25	5620	8kN		27	100	3.5
S-2310ABS	Straight gate / Self closing / Non-Locking	25	5620	10kN	8kN	29	87	3.1

* S-2310ABS is without EN362 certification

S-2697IS "MODIFIED-D" STAINLESS STEEL CARABINER

Minimum breaking strength : ⚡ 60kN / 13489LBS ⚡ 16kN ↪ 18kN
Material : High tensile stainless steel 630 / 17-4PH
Standard finish : Self colored
Weight : 251g / 8.8oz
Optional captive pin available



S50-2697I "MODIFIED-D" STAINLESS STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS
Minimum breaking strength : ⚡ 60kN / 13489LBS ⚡ 16kN ↪ 18kN
Material : High tensile stainless steel 630 / 17-4PH
Standard finish : Self colored
Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2697I	Twist lock / Self locking	293	10.3
S50-2697IT	Triple lock / Self locking	291	10.2



S-2819 "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : ⚡ 28kN / 6295LBS ⚡ 9kN ↪ 10kN
Material : Aluminum alloy
Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2819S	Screw lock / Manual locking	90	3.2
S-2819	Twist lock / Self locking	97	3.4
S-2819T	Triple lock / Self locking	98	3.5



CARABINERS

(Page 62)

S-2638A "MODIFIED-D" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacktriangleleft$ 36kN / 8094LBS $\blacktriangleright$ 8kN $\curvearrowright$ 13kN

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2638AS	Screw lock / Manual locking	99	3.5
S-2638A	Twist lock / Self locking	107	3.8
S-2638AT	Triple lock / Self locking	108	3.8




S-2638AS



S-2638A



S-2638AT



S36-2806 FORGED "MODIFIED-D" ALUMINUM CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacktriangleleft$ 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Anodized

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S36-2806	Twist lock / Self locking	136	4.8
S36-2806T	Triple lock / Self locking	137	4.8



S36-2806



S36-2806T



S36-2646 FORGED "MODIFIED-D" ALUMINUM CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacktriangleleft$ 24kN / 5395LBS

Material : Aluminum alloy

Standard finish : Anodized

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S36-2646	Twist lock / Self locking	148	5.2
S36-2646T	Triple lock / Self locking	147	5.2



S36-2646



S36-2646T



S-2690S "MODIFIED-D" STEEL CARABINER

Gate mechanism : Screw lock / Manual Locking


Minimum breaking strength : $\blacktriangleleft$ 54kN / 12140LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 343g / 12oz

Optional captive pin available



CARABINERS

(Page 63)

S36-2690 "MODIFIED-D" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 54kN / 12140LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S36-2690	Twist lock / Self locking	404	14.2
S36-2690T	Triple lock / Self locking	404	14.2



S36-2690

S36-2690T




S-2004 "KLETTERSTEIG" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 41kN / 9217LBS $\blacklozenge$ 9kN $\curvearrowright$ 12kN

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight		Certifications		
		G	(g)	(oz)	CE EN362	CE EN12275	UIAA
S-2004S	Screw lock / Manual locking	27	236	8.3	•	•	•
S-2004	Twist lock / Self locking	25	259	9.1	•		
S-2004T	Triple lock / Self locking	25	257	9.1	•		

* S-2004T not shown



S-2004S

S-2004

S50-2004 "KLETTERSTEIG" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 41kN / 9217LBS

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight		Certifications	
		(g)	(oz)	CE EN362	CS US
S50-2004	Twist lock / Self locking	281	9.9	•	•
S50-2004T	Triple lock / Self locking	279	9.8	•	

* S50-2004T not shown



S50-2004

S-2004K "KLETTERSTEIG" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 12kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2004KS	Screw lock / Manual locking	28	242	8.5
S-2004K	Twist lock / Self locking	28	262	9.2
S-2004KT	Triple lock / Self locking	27	261	9.2



S-2004KS

S-2004K

S-2004KT

CARABINERS

(Page 64)

S50-2004K "KLETTERSTEIG" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 12kN

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)		Weight	
		G		(g)	(oz)
S50-2004K	Twist lock / Self locking	22		311	11.0
S50-2004KT	Triple lock / Self locking	23		315	11.1

* S50-2004KT not shown



S50-2004K

S-2081 "HMS" ALUMINUM CARABINERS (3 models)


Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	$\blacklozenge$		$\blacklozenge$	$\curvearrowright$	Dimension (mm)		Weight	
		(kN)	(lbs)			G		(g)	(oz)
S-2081S	Screw lock / Manual locking	24	5395	7kN	6kN	23		89	3.1
S-2081	Twist lock / Self locking	25	5620	7kN		21		96	3.4
S-2081T	Triple lock / Self locking	25	5620	7kN		21		96	3.4

* S-2081T not shown



S-2081S



S-2081

S-2290 FORGED "HMS" STEEL CARABINERS (3 models)


Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 16kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Dimension (mm)		Weight	
		G		(g)	(oz)
S-2290S	Screw lock / Manual locking	24		234	8.3
S-2290	Twist lock / Self locking	23		252	8.9
S-2290T	Triple lock / Self locking	23		275	9.7



S-2290S



S-2290



S-2290T

S50-2290 FORGED "HMS" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 16kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Dimension (mm)		Weight	
		G		(g)	(oz)
S50-2290	Twist lock / Self locking	22		275	9.7
S50-2290T	Triple lock / Self locking	21		275	9.7

* S50-2290 not shown




S50-2290T



S-2290A FORGED "HMS" ALUMINUM CARABINERS (3 models)

Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	$\blacklozenge$		$\blacklozenge$	$\curvearrowright$	Weight	
		(kN)	(lbs)			(g)	(oz)
S-2290AS	Screw lock / Manual locking	22	5000	10kN	8kN	89	3.1
S-2290A	Twist lock / Self locking	22	5000	8kN		95	3.4
S-2290AT	Triple lock / Self locking	22	5000	8kN		95	3.4



S-2290AS



S-2290A




S-2290AT

CARABINERS

(Page 65)

S-2319A "HMS" ALUMINUM CARABINERS (3 models)

Material : Aluminum alloy
Standard finish : Anodized



Model	Gate mechanism	Strength		Gate	Lock	Dimension (mm)	Weight	
		(kN)	(lbs)			G	(g)	(oz)
S-2319AS	Screw lock / Manual locking	24	5395	10kN	6kN	24	86	3
S-2319A	Twist lock / Self locking	24	5395	8kN		23	94	3.3
S-2319AT	Triple lock / Self locking	24	5395	8kN		23	95	3.4




S-2319AS

S-2319A

S-2319AT

S-2196O FORGED "HMS" ALUMINUM CARABINERS (3 models)

Material : Aluminum alloy
Standard finish : Anodized



Model	Gate mechanism	Strength		Gate	Lock	Weight	
		(kN)	(lbs)			(g)	(oz)
S-2196OS	Screw lock / Manual locking	22	5000	10kN	8kN	93	3.3
S-2196O	Twist lock / Self locking	22	5000	9kN		93	3.3
S-2196OT	Triple lock / Self locking	22	5000	9kN		87	3.1

* S-2196OT not shown




S-2196OS

S-2196O

S-2196OBS FORGED "HMS" ALUMINUM CARABINER

Gate mechanism : Straight gate / Self closing / Non-Locking
Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS $\blacklozenge$ 10kN $\curvearrowright$ 7kN
Material : Aluminum alloy
Standard finish : Anodized
Weight : 81g / 2.9oz



S36-2371 FORGED "HMS" ALUMINUM CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : Aluminum alloy
Standard finish : Anodized




Model	Gate mechanism	Dimension (mm)	Weight		UKCA
		G	(g)	(oz)	
S36-2371	Twist lock / Self locking	19	130	4.6	•
S36-2371T	Triple lock / Self locking	18	136	4.8	

* S36-2371T not shown



S36-2371



S36-2371K FORGED "HMS" ALUMINUM CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 27kN / 6070LBS

Material : Aluminum alloy
Standard finish : Anodized




Model	Gate mechanism	Weight	
		(g)	(oz)
S36-2371K	Twist lock / Self locking	136	4.8
S36-2371KT	Triple lock / Self locking	136	4.8

* S36-2371KT not shown



S36-2371KT



CARABINERS

(Page 66)


S-2010 "HMS" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 35kN / 7868LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2010	Twist lock / Self locking	27	294	6.8
S-2010T	Triple lock / Self locking	27	292	6.7
S-2010S	Screw lock / Manual locking	28	274	6.1


* S-2010T not shown



S-2010S



S-2010



S50-2010 "HMS" STEEL CARABINERS (2 models)


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 35kN / 7868LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2010	Twist lock / Self locking	314	11.1
S50-2010T	Triple lock / Self locking	312	11

* S50-2010T not shown



S50-2010



S-2010I "HMS" STAINLESS STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile stainless steel

Standard finish : Chrome plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2010I	Twist lock / Self locking	294	6.8
S-2010IT	Triple lock / Self locking	292	6.7
S-2010IS	Screw lock / Manual locking	274	6.1


* S-2010I not shown



S-2010IS



S-2010IT



S50-2010I "HMS" STAINLESS STEEL CARABINERS (2 models)

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS

Material : High tensile stainless steel

Standard finish : Chrome plate

Optional captive pin available




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2010I	Twist lock / Self locking	314	11.1
S50-2010IT	Triple lock / Self locking	312	11.0

* S50-2010IT not shown



S50-2010I



S-2010K "HMS" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 16kN $\curvearrowright$ 10kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2010KS	Screw lock / Manual locking	30	278	9.8
S-2010K	Twist lock / Self locking	29	298	10.5
S-2010KT	Triple lock / Self locking	29	298	10.5



S-2010KS



S-2010K



S-2010KT

CARABINERS

(Page 67)

S50-2010K "HMS" STEEL CARABINERS (2 models)

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 16kN $\curvearrowright$ 10kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2010K	Twist lock / Self locking	319	11.3
S50-2010KT	Triple lock / Self locking	319	11.3



S50-2010K

S50-2010KT

S-2197O "HMS" STEEL CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 10kN $\curvearrowright$ 15kN



Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S-2197O	Twist lock / Self locking	28	303	10.7
S-2197OT	Triple lock / Self locking	28	301	10.6
S-2197OS	Screw lock / Manual locking	30	280	9.9

* S-2197O not shown



S-2197OS

S-2197OT

S50-2197O "HMS" STEEL CARABINERS (2 models)

Gate strength : 16kN / 3600LBS


Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2197O	Twist lock / Self locking	322	11.4
S50-2197OT	Triple lock / Self locking	320	11.3



S50-2197O

S50-2197OT

S-2197K "HMS" STEEL CARABINERS (3 models)


Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 15kN

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2197KS	Screw lock / Manual locking	278	9.8
S-2197K	Twist lock / Self locking	298	10.5
S-2197KT	Triple lock / Self locking	298	10.5



S-2197KS

S-2197K

S-2197KT

S50-2197K "HMS" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 16kN $\curvearrowright$ 15kN


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive pin available



Model	Gate mechanism	Dimension (mm)	Weight	
		G	(g)	(oz)
S50-2197K	Twist lock / Self locking	23	362	12.8
S50-2197KT	Triple lock / Self locking	22	366	12.9



S50-2197K


S50-2197KT

CARABINERS

(Page 68)

S-2805S FORGED "HMS" STEEL CARABINER

Gate mechanism : Screw lock / Manual Locking
 Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 345g / 12.2oz



S50-2805 FORGED "HMS" STEEL CARABINERS (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate




Model	Gate mechanism	Weight	
		(g)	(oz)
S50-2805	Twist lock / Self locking	382	13.5
S50-2805T	Triple lock / Self locking	381	13.4

* S50-2805T not shown



S50-2805




S-2804 FORGED "HMS" ALUMINUM CARABINERS (3 models)

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
 Material : Aluminum alloy
 Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2804S	Screw lock / Manual locking	119	4.2
S-2804	Twist lock / Self locking	125	4.4
S-2804T	Triple lock / Self locking	128	4.5



S-2804S




S-2804



S-2804T


S-2755 "HMS" ALUMINUM CARABINER

Gate mechanism : Bent gate / Self closing / Non-Locking
 Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 84g / 3.0oz



S-2194AWB ALUMINUM "PADDLE" CARABINER

Gate mechanism : Bent wire / Self closing / Non-Locking
 Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS $\blacklozenge$ 8kN $\curvearrowright$ 7kN
 Material : Aluminum alloy
 Standard finish : Anodized
 Weight : 77g / 2.7oz



Large gate opening designed to secure kayak paddles.
 Fits most paddle shafts. Also rated for climbing.

CARABINERS / SLINGS

(Page 69)

S-2734T FORGED "SQUARE" STEEL CARABINER


Gate mechanism : Triple lock / Self locking

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 189g / 6.7oz



S-2713 FORGED ALUMINUM CARABINERS WITH CAPTIVE WIRE GATES (2 models)

Minimum breaking strength : $\blacklozenge$ 20kN / 4496LBS $\blacktriangle$ 20kN $\blacklozenge$ 15kN $\curvearrowright$ 7kN


Material : Aluminum alloy

Standard finish : Anodized



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2713	Twist lock / Self locking	119	4.2
S-2713T	Triple lock / Self locking	118	4.2

* S-2713 not shown





689P10 QUICKDRAW SLING 16mm

Length : 10cm

Minimum breaking strength : $\blacklozenge$ 22kN / 5000LBS

Material : Polyamide

Weight : 13g / 0.5oz




LARGE CARABINERS

(Page 70)


S-2079 ALUMINUM "LADDER" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
Minimum breaking strength : $\blacklozenge$ 27kN / 6070LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 302g / 10.7oz



S-2111 STEEL "LADDER" HOOK WITH CAPTIVE PIN


Gate mechanism : Twist lock / Self locking
Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 561g / 19.8oz



S36-2111 STEEL "LADDER" HOOK WITH CAPTIVE PIN

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Twist lock / Self locking
Gate strength : 16kN / 3600LBS
Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 608g / 21.4oz




CE EN362 UK CA  ANSI Z359.12
CSA Z259.12

S36-2111I STAINLESS STEEL "LADDER" HOOK WITH CAPTIVE PIN


Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism: Twist lock / Self locking
Gate strength : 16kN / 3600LBS
Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
Material : High tensile stainless steel 420J2
Standard finish : Chrome plate
Weight : 600g / 21.2oz




S-2111A ALUMINUM "LADDER" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 239g / 8.4oz



S-2071IS STAINLESS STEEL "LADDER" HOOK WITH CAPTIVE PIN

Gate mechanism: Screw lock / Manual locking
Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS
Material : High tensile stainless steel 630 / 17-4PH
Standard finish : Self colored
Weight : 369g / 13.0oz



CE EN362 UK CA

LARGE CARABINERS

(Page 71)

S36-2071I STAINLESS STEEL "LADDER" HOOKS WITH CAPTIVE PIN (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS



Material : High tensile stainless steel 630 / 17-4PH

Standard finish : Self colored



Model	Gate mechanism	Weight	
		(g)	(oz)
S36-2071I	Twist lock / Self locking	447	15.8
S36-2071IT	Triple lock / Self locking	447	15.8

* S36-2071I not shown




S-2071 STEEL "LADDER" HOOKS WITH CAPTIVE PIN (3 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S-2071S	Screw lock / Manual locking	369	13
S-2071	Twist lock / Self locking	408	14.4
S-2071T	Triple lock / Self locking	406	14.3

* S-2071S CE certified model reference is S-2072
* S-2071T not shown



S36-2071 STEEL "LADDER" HOOKS WITH CAPTIVE PIN (2 models)

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS



Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight		Certifications	
		(g)	(oz)	CE EN362	UK CA US
S36-2071	Twist lock / Self locking	443	15.6	•	•
S36-2071T	Triple lock / Self locking	441	15.6	•	•

* S36-2071 not shown



S-2071A STEEL "LADDER" HOOKS WITH CAPTIVE PIN (3 models)


Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Model	Gate mechanism	Weight	
		(g)	(oz)
S-2071AS	Screw lock / Manual locking	370	13.1
S-2071A	Twist lock / Self locking	409	14.4
S-2071AT	Triple lock / Self locking	407	14.3

* S-2071AT not shown



LARGE CARABINERS

(Page 72)

S-2071K STEEL "LADDER" HOOKS WITH CAPTIVE PIN (3 models)

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight		Certification
		(g)	(oz)	
S-2071KS	Screw lock / Manual locking	388	13.7	•
S-2071K	Twist lock / Self locking	412	14.6	
S-2071KT	Triple lock / Self locking	413	14.6	

* S-2071K not shown



S36-2071K STEEL "LADDER" HOOKS WITH CAPTIVE PIN (2 models)

Gate strength : 16kN / 3600LBS


Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight		Certification
		(g)	(oz)	
S36-2071K	Twist lock / Self locking	445	15.7	•
S36-2071KT	Triple lock / Self locking	446	15.8	



S-2935S STEEL "LADDER" HOOK WITH CAPTIVE PIN



Gate mechanism: Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 508g / 17.9oz



S36-2935 STEEL "LADDER" HOOKS WITH CAPTIVE PIN (2 models)

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate



Model	Gate mechanism	Weight	
		(g)	(oz)
S36-2935	Twist lock / Self locking	640	22.6
S36-2935T	Triple lock / Self locking	637	22.5

* S36-2935 not shown




LARGE CARABINERS

(Page 73)


S-2188 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
 Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 563g / 19.9oz





S36-2188 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
 Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 610g / 21.5oz





S-2189O STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
 Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Optional captive plastic eye with S-2235
 Weight : 595g / 21oz




S36-2189O STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
 Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Optional captive plastic eye with S-2235
 Weight : 642g / 22.6oz



S-2003 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN


Gate mechanism : Twist lock / Self locking
 Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Optional captive plastic eye with S-2235
 Weight : 717g / 25.3oz



S36-2003 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Twist lock / Self locking
 Gate strength : 16kN / 3600LBS
 Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
 Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Optional captive plastic eye with S-2235
 Weight : 779g / 27.5oz




LARGE CARABINERS

(Page 74)


S-2151 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 723g / 25.5oz



S-2151T STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN


Gate mechanism : Triple lock / Self locking
Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 718g / 25.3oz



S36-2151 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN


Meets ANSI Z359.12-2019 / CSA Z259.12-2016

Gate mechanism : Twist lock / Self locking
Gate strength : 16kN / 3600LBS
Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 787g / 27.8oz





S-2151A ALUMINUM "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 348g / 12.3oz




S-2113E ALUMINUM "SCAFFOLD" HOOK WITH CAPTIVE LATCH

Gate mechanism : Express lock / Self locking
Minimum breaking strength : $\blacklozenge$ 23kN / 5171LBS
Material : Aluminum alloy
Standard finish : Anodized
Weight : 243g / 8.6oz



S-2712 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking
Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 750g / 26.5oz



LARGE CARABINERS

(Page 75)

S36-2712 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 813g / 28.7oz



S-2012 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking


Minimum breaking strength : $\blacklozenge$ 35kN / 7868LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive plastic eye with S-2235

Weight : 746g / 26.3oz



S-2012T STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Triple lock / Self locking


Minimum breaking strength : $\blacklozenge$ 35kN / 7868LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive plastic eye with S-2235

Weight : 742g / 26.2oz



S36-2012 STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking

Gate strength : 16kN / 3600LBS


Minimum breaking strength : $\blacklozenge$ 35kN / 7868LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive plastic eye with S-2235

Weight : 811g / 28.6oz



S-2009 ALUMINUM "SCAFFOLD" HOOK WITH CAPTIVE PIN


Gate mechanism : Twist lock / Self locking

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 360g / 12.7oz



S36-2009 FORGED ALUMINUM "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 447g / 15.8oz



LARGE CARABINERS / QUICK LINKS

(Page 76)

S36-2009T FORGED ALUMINUM "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Triple lock / Self locking


Gate strength : 16kN / 3600LBS

Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 465g / 16.4oz



S-2190O STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking



Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive plastic eye with S-2235

Weight : 745g / 26.3oz



S36-2190O STEEL "SCAFFOLD" HOOK WITH CAPTIVE PIN

Gate mechanism : Twist lock / Self locking

Gate strength : 16kN / 3600LBS



Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Optional captive plastic eye with S-2235

Weight : 809g / 28.5oz



S-2235 REMOVEABLE CAPTIVE PLASTIC EYE

For S-2012, S36-2012, S-2003, S36-2003, S-2189O, S36-2189O, S-2190O and S36-2190O.

Available in any color

Weight : 5.3g / 0.2oz



Glow in the dark neon colors available!



6636-7 STEEL "SQUARE" QUICK LINK



Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS $\blacklozenge$ 10kN

Material : Steel

Standard finish : Silver zinc plate

Weight : 73g / 2.6oz



6636I6-7 STAINLESS STEEL "SQUARE" QUICK LINK



Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS $\blacklozenge$ 10kN

Material : Stainless steel 316

Standard finish : Self colored

Weight : 72g / 2.5oz





QUICK LINKS

(Page 77)



7352-8 STEEL "OVAL" QUICK LINK

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 10kN
 Material : Steel
 Standard finish : Silver zinc plate
 Weight : 93g / 3.3oz





7352I6-8 STAINLESS STEEL "OVAL" QUICK LINK

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 35kN / 7868LBS $\blacklozenge$ 10kN
 Material : Stainless steel 316
 Standard finish : Self colored
 Weight : 95g / 3.4oz





7350-8 STEEL "OVAL" QUICK LINK

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 30kN / 6744LBS $\blacklozenge$ 10kN
 Material : Steel
 Standard finish : Silver zinc plate
 Weight : 73g / 2.6oz





7350I6-8 STAINLESS STEEL "OVAL" QUICK LINK

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS $\blacklozenge$ 10kN
 Material : Stainless steel 316
 Standard finish : Self colored
 Weight : 79g / 2.8oz





7360-8 STEEL "DELTA" QUICK LINK

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 25kN / 5620LBS $\blacklozenge$ 10kN
 Material : Steel
 Standard finish : Silver zinc plate
 Weight : 87g / 3.1oz



7360I6-8 STAINLESS STEEL "DELTA" QUICK LINK

Gate mechanism : Screw lock / Manual locking
 Minimum breaking strength : $\blacklozenge$ 40kN / 8992LBS $\blacklozenge$ 10kN
 Material : Stainless steel 316
 Standard finish : Self colored
 Weight : 86g / 3.0oz



QUICK LINKS

(Page 78)

7350-10 STEEL "OVAL" QUICK LINK



Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 50kN / 11240LBS $\blacklozenge$ 10kN

Material : Steel

Standard finish : Silver zinc plate

Weight : 153g / 5.4oz



7350I6-10 STAINLESS STEEL "OVAL" QUICK LINK



Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 70kN / 15736LBS $\blacklozenge$ 10kN

Material : Stainless steel 316

Standard finish : Self colored

Weight : 154g / 5.4oz



7360-10 STEEL "DELTA" QUICK LINK



Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 45kN / 10116LBS $\blacklozenge$ 10kN

Material : Steel

Standard finish : Silver zinc plate

Weight : 169g / 6.0oz



7360I6-10 STAINLESS STEEL "DELTA" QUICK LINK



Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : $\blacklozenge$ 65kN / 14612LBS $\blacklozenge$ 10kN

Material : Stainless steel 316

Standard finish : Self colored

Weight : 168g / 5.9oz



DESCENDERS

(Page 79)


S-2199 ALUMINUM DESCENDER WITH ANTI-PANIC SYSTEM FOR WORK AT HEIGHT AND EMERGENCY SELF EVACUATION

Material : Aluminum alloy
Standard finish : Anodized
EN341 Class A rope size : Ø10.5mm to Ø11mm
EN12841 Class C rope size : Ø10mm to Ø13mm
Weight : 465g / 16.4oz




S-2091 FORGED ALUMINUM FIGURE-8 DESCENDER

Minimum breaking strength : 35kN / 7868LBS
Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø7.7mm to Ø11mm
Weight : 108g / 3.8oz




S-2091A FORGED ALUMINUM FIGURE-8 DESCENDER

Minimum breaking strength : 28kN / 6294LBS
Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø9mm to Ø12mm
Weight : 101g / 3.6oz




S-2640 FORGED ALUMINUM FIGURE-8 DESCENDER

Minimum breaking strength : 35kN / 7868LBS
Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø9mm to Ø12mm
Weight : 116g / 4.1oz



S-2124 FORGED ALUMINUM FIGURE-8 DESCENDER

Minimum breaking strength : 35kN / 7868LBS
Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø7.7mm to Ø11mm
Weight : 123g / 4.3oz



DESCENDERS

(Page 80)

S-2124C STEEL FIGURE-8 DESCENDER

Minimum breaking strength : 35kN / 7868LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Chrome plate

Rope size : Ø9mm to Ø12mm

Weight : 329g / 11.6oz



S-2124I STAINLESS STEEL FIGURE-8 DESCENDER


Minimum breaking strength : 40kN / 8992LBS

Material : Stainless steel 304

Standard finish : Self colored

Rope size : Ø9mm to Ø12mm

Weight : 333g / 11.7oz



S-2092 FORGED ALUMINUM FIGURE-8 DESCENDER


Minimum breaking strength : 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø8.1mm to Ø11mm

Weight : 89g / 3.1oz



S-2272 SMALL FORGED STEEL RESCUE FIGURE-8 DESCENDER

Minimum breaking strength : 40kN / 8992LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Chrome plate

Rope size : Ø9mm to Ø16mm

Weight : 451g / 15.9oz



S-2272A SMALL FORGED ALUMINUM RESCUE FIGURE-8 DESCENDER


Minimum breaking strength : 40kN / 8992LBS

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø9mm to Ø16mm

Weight : 154g / 5.4oz



DESCENDERS

(Page 81)

S-22721 SMALL FORGED STAINLESS STEEL RESCUE FIGURE-8 DESCENDER


Minimum breaking strength : 40kN / 8992LBS

Material : Stainless steel 304

Standard finish : Self colored

Rope size : Ø9mm to Ø16mm

Weight : 459g / 16.2oz



S-2269 LARGE FORGED STEEL RESCUE FIGURE-8 DESCENDER

Minimum breaking strength : 67kN / 15026LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Chrome plate

Rope size : Ø9mm to Ø19mm

Weight : 737g / 26oz



S-2208 FORGED LARGE ALUMINUM RESCUE FIGURE-8 DESCENDER


Minimum breaking strength : 40kN / 8992LBS

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø9mm to Ø16mm

Weight : 257g / 9.1oz



S-22081 LARGE STAINLESS STEEL RESCUE FIGURE-8 DESCENDER


Minimum breaking strength : 50kN / 11240LBS

Material : Stainless steel 304

Standard finish : Self colored

Rope size : Ø9mm to Ø16mm

Weight : 768g / 27.1oz




S-2431 STEEL DESCENDER RACK

Material : High tensile steel

Standard finish : Black E-Coat / Black oxide

Weight : 602g / 21.2oz




DESCENDERS

(Page 82)



S-2309 BELAY (STICHT) PLATE

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø8mm to Ø11mm
Weight : 64g / 2.3oz




S-2309S BELAY (STICHT) PLATE WITH SPRING

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø8mm to Ø11mm
Weight : 84g / 3oz




S-2267 BELAY TUBE / DOUBLE SLOT

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø7.7mm to Ø11mm
Weight : 54g / 1.9oz




S-2282 BELAY TUBE / DOUBLE SLOT

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø7.7mm to Ø11mm
Weight : 74g / 2.6oz



S-2313 BELAY TUBE / DOUBLE SLOT

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø7.7mm to Ø11mm
Weight : 92g / 3.2oz




DESCENDERS / ASCENDERS

(Page 83)


S-2316 BELAY TUBE / SINGLE SLOT

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø7.7mm to Ø11mm
Weight : 56g / 2oz




S-2324 BELAY TUBE / DOUBLE SLOT

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø7.7mm to Ø11mm
Weight : 93g / 3.3oz




S-8088L V2 HANDLED ASCENDER / LEFT HAND

Material : Aluminum alloy
Standard finish : Anodized
EN12841 Class B rope size : Ø10mm to Ø13mm
EN567 rope size : Ø9mm to Ø13mm
Weight : 246g / 8.7oz




S-8088R V2 HANDLED ASCENDER / RIGHT HAND

Material : Aluminum alloy
Standard finish : Anodized
EN12841 Class B rope size : Ø10mm to Ø13mm
EN567 rope size : Ø9mm to Ø13mm
Weight : 246g / 8.7oz



S-8088L HANDLED ASCENDER / LEFT HAND

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø8mm to Ø13mm
Weight : 238g / 8.4oz





ASCENDERS

(Page 84)



S-8088R HANDLED ASCENDER / RIGHT HAND

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø8mm to Ø13mm
Weight : 238g / 8.4oz




S-8088CL CHEST ASCENDER

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø8mm to Ø13mm
Weight : 159g / 5.6oz




S-8088CBL V2 CHEST ASCENDER

Material : Aluminum alloy
Standard finish : Anodized
EN12841 Class B rope size : Ø10mm to Ø13mm
EN567 rope size : Ø9mm to Ø13mm
Weight : 175g / 6.2oz



S-8088CBL CHEST ASCENDER

Material : Aluminum alloy
Standard finish : Anodized
Rope size : Ø8mm to Ø13mm
Weight : 171g / 6.0oz



ASCENDERS / ROPE GRABS

(Page 85)

S-8088W45L V2 ASCENDER WITH WEB SLOT / 45mm



Material : Aluminum alloy

Standard finish : Anodized

EN12841 Class B rope size : Ø10mm to Ø13mm

EN567 rope size : Ø9mm to Ø13mm

Weight : 173g / 6.1oz




S-8088W45L ASCENDER WITH WEB SLOT / 45mm

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø8mm to Ø13mm

Weight : 168g / 5.9oz



S-2924 ASCENDING ROPE GRAB WITH SPRING LOADED CAM



Component for fall arrest/work positioning system¹

Material : Aluminum alloy / Stainless steel 304 / Plastic grip

Standard finish : Anodized

Rope size : Ø8mm - Ø14mm

Weight : 223g / 7.9oz



S-2709 ASCENDING ROPE GRAB WITH SPRING LOADED CAM



Component for fall arrest/work positioning system¹

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø8mm - Ø13mm

Weight : 189g / 6.7oz



S-2738 ASCENDING ROPE GRAB WITH SPRING LOADED CAM

Component for fall arrest/work positioning system¹



Material : Aluminum alloy / Stainless steel 304 / Plastic grip

Standard finish : Anodized

Rope size : Ø8mm - Ø13mm

Weight : 235g / 8.3oz

Not available in EUROPE



⁽¹⁾ Cable/Rope grab may be used as a component in a fall arrest or work positioning system. To ensure its suitability and compatibility, when incorporated into a fall arrest or work positioning system, it must be tested, together with all other components (Carabiner, snaphook, rope/lifeline, energy absorber etc.) in the system, to the appropriate standard (ANSI, CE, CSA etc.) with positive test results. It is the system manufacturer's responsibility to perform the needed verification of component compatibility in its system(s).

ROPE GRABS

(Page 86)

S-2923 ASCENDING ROPE GRAB WITH SPRING LOADED CAM

Component for fall arrest/work positioning system¹

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø8mm - Ø16mm

Weight : 268g / 9.5oz



S-2200 ASCENDING ROPE GRABS (2 models)

Component for fall arrest/work positioning system¹

Material : Aluminum alloy


Standard finish : Anodized

Rope size : Ø9mm - Ø13mm

CAM axel options available



Model	CAM axel	Weight	
		(g)	(oz)
S-2200	Fixed bolt and nut	180	6.4
S-2200B	Ball lock pin	176	6.2



S-2200



S-2200B



S-2200T ASCENDING ROPE GRABS (2 models)

Component for fall arrest/work positioning system¹

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø9mm - Ø13mm


CAM axel options available

Model	CAM axel	Weight	
		(g)	(oz)
S-2200T	Fixed bolt and nut	190	6.7
S-2200TB	Ball lock pin	186	6.6

S-2200TB



S-2200T



S-2200TS ASCENDING ROPE GRAB WITH SPRING LOADED CAM


Component for fall arrest/work positioning system¹

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø9mm - Ø13mm

Weight : 171g / 6.0oz



S-2692 ASCENDING ROPE GRABS (2 models)

Component for fall arrest/work positioning system¹

Material : Aluminum alloy

Standard finish : Anodized

Rope size : Ø8mm - Ø16mm

Maximum web strap size : Ø30mm

CAM axel options available




S-2692



S-2692B



Model	CAM axel	Weight	
		(g)	(oz)
S-2692	Fixed bolt and nut	366	12.9
S-2692B	Ball lock pin	374	13.1



Works with webbing

⁽¹⁾ Cable/Rope grab may be used as a component in a fall arrest or work positioning system. To ensure its suitability and compatibility, when incorporated into a fall arrest or work positioning system, it must be tested, together with all other components (Carabiner, snaphook, rope/lifeline, energy absorber etc.) in the system, to the appropriate standard (ANSI, CE, CSA etc.) with positive test results. It is the system manufacturer's responsibility to perform the needed verification of component compatibility in its system(s).

ROPE GRABS

(Page 87)

S-2237 ASCENDING ROPE GRABS (2 models)

Component for fall arrest/work positioning system¹

Material : Aluminum alloy


Standard finish : Anodized

Rope size : Ø11mm - Ø16mm

CAM axel options available



Model	CAM axel	Weight	
		(g)	(oz)
S-2237	Fixed bolt and nut	311	11
S-2237B	Ball lock pin	314	11.1



S-2733 ROPE GRAB


Component for fall arrest/work positioning system¹

Material : Aluminum alloy

Standard finish : Anodized

Wire rope size : Ø11mm - Ø13mm

Weight : 154g / 5.4oz



S-2835 ROPE GRAB


Component for fall arrest/work positioning system¹

Material : Aluminum alloy

Standard finish : Anodized

Wire rope size : Ø10.5mm - Ø12.7mm

Weight : 170g / 6.0oz



S-2039 DUAL CAM CABLE GRAB

Component for fall arrest system¹


Material : Stainless steel 304

Standard finish : Self colored

Wire rope size : Ø8mm

For use with stainless or galvanized wire ropes

Weight : 474g / 16.7oz



S-2259 DUAL CAM CABLE GRAB WITH GUIDE PIN

Component for fall arrest system¹


Material : Stainless steel 304

Standard finish : Self colored

Wire rope size : Ø8mm

For use with stainless or galvanized wire ropes

Weight : 498g / 17.6oz



⁽¹⁾ Cable/Rope grab may be used as a component in a fall arrest or work positioning system. To ensure its suitability and compatibility, when incorporated into a fall arrest or work positioning system, it must be tested, together with all other components (Carabiner, snaphook, rope/lifeline, energy absorber etc.) in the system, to the appropriate standard (ANSI, CE, CSA etc.) with positive test results. It is the system manufacturer's responsibility to perform the needed verification of component compatibility in its system(s).

ROPE GRABS

(Page 88)

S-2260 DUAL CAM CABLE GRAB WITH GUIDE PIN

Component for fall arrest system¹


Material : Stainless steel 304

Standard finish : Self colored

Wire rope size : Ø10mm

For use with stainless or galvanized wire ropes

Weight : 461g / 16.3oz



S-2721 ROPE GRAB

Component for fall arrest¹


Material : Stainless steel 304

Standard finish : Self colored

Wire rope size : Ø14mm

Weight : 658g / 23.2oz

For use with synthetic ropes



S-2618 DUAL CAM ROPE GRABS (2 models)

Component for fall arrest/work positioning system¹


Material : Steel

Standard finish : Yellow / Silver zinc plate

Rope size : Ø11mm to Ø12mm

For use with synthetic ropes

Model	Dimension (mm)		Weight	
	E		(g)	(oz)
S-2618	20		380	13.4
S-2618H			449	15.8



S-963 DUAL CAM ROPE GRABS (3 models)

Component for fall arrest/work positioning system¹

Material : Steel


Standard finish : Yellow / Silver zinc plate

Chrome plate

Rope size : Ø16mm

For use with synthetic ropes

Model	Dimension (mm)		Weight	
	E		(g)	(oz)
S-963	20		447	15.8
S-963L	55		501	17.7
S-963H			550	19.4



S-2035 ROPE GRABS (4 models)

Component for fall arrest system¹


Material : Steel / Stainless steel

Rope size : Ø16mm

For use with synthetic ropes

Model	Material	Standard finish	Dimension (mm)		Weight	
			E		(g)	(oz)
S-2035	Steel	Yellow / Silver zinc plate	26		319	11.3
S-2035L	Steel	Yellow / Silver zinc plate	55		364	12.8
S-2035I	Stainless steel 304	Self colored	26		317	11.2
S-2035IL	Stainless steel 304	Self colored	55		362	12.8

* S-2035, S-2035IL not shown



(1) Cable/Rope grab may be used as a component in a fall arrest or work positioning system. To ensure its suitability and compatibility, when incorporated into a fall arrest or work positioning system, it must be tested, together with all other components (Carabiner, snaphook, rope/lifeline, energy absorber etc.) in the system, to the appropriate standard (ANSI, CE, CSA etc.) with positive test results. It is the system manufacturer's responsibility to perform the needed verification of component compatibility in its system(s).

ROPE GRABS

(Page 89)


S-2036 ROPE GRABS (4 models)

Component for fall arrest system¹

Material : Steel / Stainless steel

Rope size : Ø12mm

For use with synthetic ropes



Model	Material	Standard finish	Dimension (mm)		Weight	
			E	(g)	(oz)	
S-2036	Steel	Yellow / Silver zinc plate	26	322	11.4	
S-2036L	Steel	Yellow / Silver zinc plate	55	367	12.9	
S-2036I	Stainless steel 304	Self colored	26	323	11.4	
S-2036IL	Stainless steel 304	Self colored	55	368	13	

* S-2036L not shown



S-2036I



S-2036



S-2036IL

S-2191 DUAL CAM ROPE GRABS (4 models)

Component for fall arrest/work positioning system¹


Material : Steel / Stainless steel

Rope size : Ø12mm

For use with synthetic ropes

Model	Material	Standard finish	Dimension (mm)		Weight	
			E	(g)	(oz)	
S-2191	Steel	Yellow / Silver zinc plate	20	454	16	
S-2191L	Steel	Yellow / Silver zinc plate	55	499	17.6	
S-2191I	Stainless steel 304	Self colored	20	457	16.1	
S-2191IL	Stainless steel 304	Self colored	55	502	17.7	

* S-2191L not shown



S-2191



S-2191I



S-2191IL

S-2038 ROPE GRABS (7 models)

Component for fall arrest/work positioning system¹

Material : Steel / Stainless steel

For use with synthetic ropes



S-2038L




S-2038IL



S-2038-1I



S-2038



Model	Material	Rope size	Standard finish	Dimension (mm)		Weight	
				E	(g)	(oz)	
S-2038	Steel	Ø16mm	Yellow / Silver zinc plate	26	488	17.2	
S-2038L	Steel	Ø16mm	Yellow / Silver zinc plate	55	524	18.5	
S-2038I	Stainless steel 304	Ø16mm	Self colored	26	490	17.3	
S-2038IL	Stainless steel 304	Ø16mm	Self colored	55	523	18.4	
S-2038-1	Steel	Ø12mm	Yellow / Silver zinc plate	26	472	16.6	
S-2038-1L	Steel	Ø12mm	Yellow / Silver zinc plate	55	523	18.4	
S-2038-1I	Stainless steel 304	Ø12mm	Self colored	26	472	16.6	

* S-2038I, S-2038-1, S-2038-1L not shown

S-2037I DUAL CAM ROPE GRABS (2 models)


Component for fall arrest/work positioning system¹

Material : Stainless steel 304

Standard finish : Self colored

Rope size : Ø16mm to Ø19mm

For use with synthetic ropes



S-2037I



S-2037IL

Model	Dimension (mm)		Weight	
	E	(g)	(oz)	
S-2037I	20	719	25.4	
S-2037IL	55	764	26.9	

⁽¹⁾ Cable/Rope grab may be used as a component in a fall arrest or work positioning system. To ensure its suitability and compatibility, when incorporated into a fall arrest or work positioning system, it must be tested, together with all other components (Carabiner, snaphook, rope/lifeline, energy absorber etc.) in the system, to the appropriate standard (ANSI, CE, CSA etc.) with positive test results. It is the system manufacturer's responsibility to perform the needed verification of component compatibility in its system(s).

ROPE GRABS

(Page 90)

S-2382IL DUAL CAM ROPE GRAB WITH ANTI-PANIC SYSTEM

Component for fall arrest/work positioning system¹


Material : Stainless steel 304

Standard finish : Self colored

Rope size : Ø16mm

Weight : 744g / 26.2oz

For use with synthetic ropes



S-2074I ROPE GRAB WITH 26mm EYE

Component for fall arrest system¹


Material : Stainless steel 304

Standard finish : Self colored

Rope size : Ø16mm

For use with synthetic ropes

Weight : 476g / 16.8oz



S-2381 ROPE GRAB

Component for work positioning system¹



Material : Stainless steel 304 / Aluminum alloy

Standard finish : Self colored

Rope size : Ø14mm to Ø16mm

For use with synthetic ropes

Weight : 476g / 16.8oz



⁽¹⁾ Cable/Rope grab may be used as a component in a fall arrest or work positioning system. To ensure its suitability and compatibility, when incorporated into a fall arrest or work positioning system, it must be tested, together with all other components (Carabiner, snaphook, rope/lifeline, energy absorber etc.) in the system, to the appropriate standard (ANSI, CE, CSA etc.) with positive test results. It is the system manufacturer's responsibility to perform the needed verification of component compatibility in its system(s).

ANCHORAGE CONNECTORS

(Page 91)

S-960 REUSABLE ROOF ANCHORS [4 models]

Minimum breaking strength : 22kN / 5000LBS

Material : Steel (Welded assembly)

Standard finish : Yellow / Silver zinc plate
Lacquer coating

Model	D-Ring model	Countersunk holes	Dimension (mm) L	Weight (g) (oz)
S-960	S-938 (forged)		360	1154 40.7
S-960C	S-938 (forged)	•	360	1068 37.7
S-960S	S-2065 (stamped)		352	1107 39
S-960SC	S-2065 (stamped)	•	352	1021 36


* S-960, S-960S not shown



S-960C



S-960SC



S-960-2 REUSABLE ROOF ANCHORS [4 models]


Minimum breaking strength : 22kN / 5000LBS

Material : Steel (Welded assembly)

Standard finish : Yellow / Silver zinc plate
Lacquer coating

Model	D-Ring model	Countersunk holes	Weight (g) (oz)
S-960-2	S-938 (forged)		1186 41.8
S-960-2C	S-938 (forged)	•	1100 38.8
S-960-2S	S-2065 (stamped)		1139 40.2
S-960-2SC	S-2065 (stamped)	•	1053 37.1


* S-960-2C, S-960-2S, S-960-2SC not shown



Installable on flat surface



S-960-2



S-960-3 REUSABLE ROOF ANCHORS [4 models]


Minimum breaking strength : 22kN / 5000LBS

Material : Steel (Riveted assembly)

Standard finish : Yellow / Silver zinc plate

Model	D-Ring model	Countersunk holes	Weight (g) (oz)
S-960-3	S-938 (forged)		1093 38.6
S-960-3C	S-938 (forged)	•	1007 35.5
S-960-3S	S-2065 (stamped)		1046 36.9
S-960-3SC	S-2065 (stamped)	•	960 33.9


* S-960-3C, S-960-3S, S-960-3SC not shown



Installable on flat surface



S-960-3




S-2639 STEEL GROUND ANCHOR

Minimum breaking strength : 30kN / 6744LBS

Material : Steel

Standard finish : Hot dip galvanized zinc

Weight : 3.6kg / 7.9lb



S-2251 GIRDER GRIP

Minimum breaking strength : 25kN / 5620LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Hole size : Ø19mm to Ø28mm

Weight : 543g / 19.2oz

Meets EN795 : 3rd party tested by SATRA UK



S-2318 LARGE GIRDER GRIP



Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Hole size : Ø19mm to Ø28mm

Weight : 1165g / 41.1oz



ANCHORAGE CONNECTORS

(Page 92)

S-2336 FORGED STEEL D-BOLT ANCHOR

Minimum breaking strength : 22kN / 5000LBS


Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Hole size : 1/2" (M13)

Weight : 387g / 13.7oz

Includes grade 9 nut and lock washer



S-2344-M13 FORGED STEEL D-BOLT ANCHOR

WARNING : D-BOLT ANCHOR installation requires minimum grade 8 quality bolt with lock washer


Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Hole size : 1/2" (M13)

Weight : 604g / 21.3oz



S-2344-M16 FORGED STEEL D-BOLT ANCHOR

WARNING : D-BOLT ANCHOR installation requires minimum grade 8 quality bolt with lock washer


Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Hole size : 5/8" (M16)

Weight : 604g / 21.3oz



S-2344-M19 FORGED STEEL D-BOLT ANCHOR

WARNING : D-BOLT ANCHOR installation requires minimum grade 8 quality bolt with lock washer


Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Hole size : 3/4" (M19)

Weight : 604g / 21.3oz



S-2344I6-M16 FORGED STAINLESS STEEL D-BOLT ANCHOR

WARNING : D-BOLT ANCHOR installation requires minimum grade 8 quality bolt with lock washer


Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Hole size : 5/8" (M16)

Weight : 687g / 24.0oz



ANCHORAGE CONNECTORS / PULLEYS

(Page 93)

S-2314 STEEL BOLT ANCHORS (3 models)

Minimum breaking strength : 25kN / 5620LBS

Material : High tensile steel


Standard finish : Yellow / Silver zinc plate

Model	Dimension (mm)		Weight	
	H		(g)	(oz)
S-2314-8	Ø8		67	2.4
S-2314-10	Ø10		67	2.4
S-2314-12	Ø12		67	2.4

* S-2314-10, S-2314-12 not shown



S-2314-8



S-2314I STAINLESS STEEL BOLT ANCHORS (2 models)

Minimum breaking strength : 25kN / 5620LBS

Material : Stainless steel 304


Standard finish : Self colored

Model	Dimension (mm)		Weight	
	H		(g)	(oz)
S-2314I-10	Ø10		66	2.3
S-2314I-12	Ø12		65	2.3

* S-2314I-12 not shown



S-2314I-10



S-2403I STAINLESS STEEL BOLT ANCHORS (2 models)

Minimum breaking strength : 25kN / 5620LBS

Material : Stainless steel 304

Standard finish : Self colored


Model	Dimension (mm)		Weight	
	H		(g)	(oz)
S-2403I-10	Ø10		40	1.4
S-2403I-12	Ø12		39	1.4



S-2403I-10



S-2403I-12



S-2620 MOBILE PULLEY WITH BALL BEARING AND INTEGRAL ROPE GRAB

Minimum breaking strength : 25kN / 5620LBS




Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø8mm to Ø13mm

Weight : 398g / 14oz

Not available in RUSSIA



S-2127 BIG MOBILE DOUBLE PULLEY



Minimum breaking strength : 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø16mm

Weight : 423g / 14.9oz



PULLEYS

(Page 94)

S-2128 BIG MOBILE PULLEY




Minimum breaking strength : 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø16mm

Weight : 246g / 8.7oz



S-2642 BIG MOBILE DOUBLE PULLEY WITH BALL BEARING

Minimum breaking strength : 36kN / 8094LBS




Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø13mm

Weight : 448g / 15.8oz

Not available in RUSSIA



S-2641 BIG MOBILE PULLEY WITH BALL BEARING

Minimum breaking strength : 36kN / 8094LBS



Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø13mm

Weight : 262g / 9.2oz

Not available in RUSSIA



S-2605 MOBILE DOUBLE PULLEY WITH BALL BEARING

Minimum breaking strength : 20kN / 4496LBS



Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø11mm

Weight : 188g / 6.6oz

Not available in RUSSIA



S-2623 MOBILE SMALL PULLEY WITH BALL BEARING

Minimum breaking strength : 20kN / 4496LBS



Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø11mm

Weight : 113g / 4oz

Not available in RUSSIA



PULLEYS

(Page 95)

S-2706 FIDDLE BLOCK PULLEY WITH SWIVEL AND BALL BEARING


Minimum breaking strength : 16kN / 3600LBS

Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø10mm

Weight : 257g / 9oz



S-2122 TYROLEAN PULLEYS (2 models)


Minimum breaking strength : 24kN / 5395LBS

Material : Aluminum alloy


Standard finish : Anodized

Model	Sheave type	Max. rope size	Max. cable size	Weight	
				(g)	(oz)
S-2122	Aluminum alloy	Ø13mm		196	6.9
S-2122C	Stainless steel	Ø13mm	Ø12mm	274	9.7

* S-2122C not shown



S-2122



S-2122CB TYROLEAN PULLEY WITH BALL BEARING

Minimum breaking strength : 20kN / 4496LBS



Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø13mm

Maximum cable size : Ø12mm

Weight : 291g / 10.3oz




S-2129 FIXED SMALL PULLEYS WITH OPTIONAL BALL BEARING (2 models)


Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized



S-2129



Model	Sheave type	With ball bearing	Max. rope size	Max. cable size	Weight	
					(g)	(oz)
S-2129	Aluminum alloy		Ø13mm		85	3
S-2129CB	Stainless steel	•	Ø13mm	Ø12mm	135	4.8

* S-2129CB not shown

S-2746 FORGED MOBILE SMALL PULLEY WITH BALL BEARING



Minimum breaking strength : 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø11mm

Weight : 90g / 3.2oz



PULLEYS

(Page 96)

S-2130 MOBILE SMALL PULLEY




Minimum breaking strength : 20kN / 4496LBS

Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø11mm

Weight : 121g / 4.3oz



S-2142 MOBILE SMALL PULLEY



Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Maximum rope size : Ø13mm

Weight : 85g / 3oz



O-RINGS

(Page 97)


S-2295H FORGED STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 51g / 1.8oz




S-2243 STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 65g / 2.3oz




S-2261 FORGED STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 82g / 2.9oz




S-2261I6 FORGED STAINLESS STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 86g / 3oz




S-954 FORGED STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 134g / 4.7oz




S-954I FORGED STAINLESS STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 134g / 4.7oz



ANSI Z359.12
CSA Z259.12



ANSI Z359.12
CSA Z259.12



ANSI Z359.12
CSA Z259.12

O-RINGS

(Page 98)


S-95416 FORGED STAINLESS STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 138g / 4.8oz




S-2681 STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 81g / 2.8oz




S-2681P STEEL O-RING PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 92g / 3.2oz




S-2306 FORGED STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 147g / 5.2oz




S-2153 FORGED STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 176g / 6.2oz




S-2630 STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 108g / 3.8oz



O-RINGS / D-RINGS

(Page 99)


S-2413 STEEL O-RING

Minimum breaking strength : 45kN / 10116LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 277g / 9.8oz



S-2826 / S-2828 / S-2834 / S-2840 / S-2857


CNC ALUMINUM O-RINGS (5 models)

Minimum breaking strength : 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Model	Dimensions (mm)			Weight		Certification
	A	B	C	(g)	(oz)	
S-2826	Ø12	50	26	42	1.5	
S-2828	Ø12	52	28	43	1.5	
S-2834	Ø12	58	34	49	1.7	
S-2840	Ø12	64	40	56	2.0	
S-2857	Ø12.5	82	57	75	2.6	




S-954PVC PVC COATED FORGED STEEL O-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 149g / 5.2oz




S-2933 FORGED ALUMINUM D-RING / 28mm

Minimum breaking strength : 24kN / 5395LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 18g / 0.6oz




S-2311 FORGED STEEL D-RING / 28mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 31g / 1.1oz




S-2162 WELDED STAINLESS STEEL D-RING / 40mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 33g / 1.2oz



D-RINGS

(Page 100)


S-2104 FORGED STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 54g / 1.9oz




S-565 FORGED STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 73g / 2.6oz



ANSI Z359.12
CSA Z259.12


S-565I4 FORGED STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 83g / 2.9oz




S-565I6 FORGED STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 85g / 2.9oz




S-565BT FORGED BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 80g / 2.8oz




S-2680 STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 76g / 2.6oz



ANSI Z359.12
CSA Z259.12

D-RINGS

(Page 101)


S-2680P STEEL D-RING PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 86g / 3oz




S-2289 WELDED STEEL D-RING / 45mm

Minimum breaking strength : 30kN / 6744LBS

Material : Steel

Standard finish : Yellow / Silver zinc plate

Weight : 67.5g / 2.4oz




S-2289I WELDED STAINLESS STEEL D-RING / 45mm

Minimum breaking strength : 30kN / 6744LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 69g / 2.4oz




S-2100 STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 48g / 1.7oz




S-2742 FORGED ALUMINUM D-RING / 45mm

Minimum breaking strength : 27kN / 6070LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 70g / 2.5oz




S-2742BT FORGED BENT ALUMINUM D-RING / 45mm

Minimum breaking strength : 27kN / 6070LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 70g / 2.5oz



D-RINGS

(Page 102)


S-2246 STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 81g / 2.9oz




S-2262 FORGED STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 117g / 4.1oz



S-2847 WELDED STEEL D-RING / 50mm


Minimum breaking strength : 22kN / 5000LBS

Material : Steel

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 170g / 6.0oz




S-2602 FORGED ALUMINUM D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 65g / 2.3oz




S-2602BT FORGED BENT ALUMINUM D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 65g / 2.3oz




S-2022 FORGED ALUMINUM D-RING / 45mm

Minimum breaking strength : 12kN / 2698LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 46g / 1.6oz



D-RINGS / SINGLE SLOT D-RINGS

(Page 103)


S-2057 FORGED STEEL D-RING / 75mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 159g / 5.6oz




S-565PVC PVC COATED FORGED STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 93g / 3.3oz




S-2028 FORGED SINGLE SLOT STEEL D-RING / 28mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 121g / 4.3oz




S-562 FORGED SINGLE SLOT STEEL D-RING / 30mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 103g / 3.6oz




S-964 SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 73g / 2.6oz




S-955 FORGED SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 105g / 3.7oz



SINGLE SLOT D-RINGS

(Page 104)


S-9551 FORGED SINGLE SLOT STAINLESS STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 115g / 4.1oz




S-95514 FORGED SINGLE SLOT STAINLESS STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 110g / 3.8oz




S-955BT FORGED SINGLE SLOT BENT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 117g / 4.1oz




S-2396 FORGED SINGLE SLOT ALUMINUM D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 64g / 2.3oz




S-2396BT FORGED SINGLE SLOT BENT ALUMINUM D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 64g / 2.3oz




S-2821 SINGLE SLOT ALUMINUM D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 56g / 2.0oz



SINGLE SLOT D-RINGS

(Page 105)


S-2317 FORGED SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 65g / 2.3oz




S-2234 SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 68g / 2.4oz




S-2234I SINGLE SLOT STAINLESS STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 72g / 2.5oz




S-2234BT SINGLE SLOT BENT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 73g / 2.6oz




S-2657P SINGLE SLOT STEEL D-RING PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 75g / 2.6oz




S-2657BTP SINGLE SLOT BENT STEEL D-RING PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 75g / 2.6oz



SINGLE SLOT D-RINGS

(Page 106)


S-2192 FORGED SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 30kN / 6744LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 67g / 2.4oz




S-2117 SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 30kN / 6744LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 75g / 2.6oz




S-2117I4 SINGLE SLOT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 72g / 2.5oz




S-2117BT SINGLE SLOT BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 75g / 2.6oz




S-2117I4BT SINGLE SLOT BENT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 72g / 2.5oz




S-2265 SINGLE SLOT STEEL D-RING WITH TANG / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 92g / 3.2oz



SINGLE SLOT D-RINGS

(Page 107)


S-2265I4 SINGLE SLOT STAINLESS STEEL D-RING WITH TANG / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 88g / 3.1oz




S-2063 SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 102g / 3.6oz




S-2063BT SINGLE SLOT BENT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 102g / 3.6oz




S-2875 FORGED SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 124g / 4.4oz




S-2875BT FORGED SINGLE SLOT BENT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 124g / 4.4oz




S-2307 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 121g / 4.3oz



SINGLE SLOT D-RINGS

(Page 108)


S-2339 FORGED SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 117g / 4.1oz




S-2339BT FORGED SINGLE SLOT BENT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 117g / 4.1oz




S-938 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 157g / 5.5oz




S-938BT FORGED SINGLE SLOT BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 145g / 5.1oz




S-2332 FORGED SINGLE SLOT ALUMINUM D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 73g / 2.6oz




S-2332BT FORGED SINGLE SLOT BENT ALUMINUM D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 70g / 2.5oz



SINGLE SLOT D-RINGS

(Page 109)


S-2332BT7 FORGED SINGLE SLOT BENT ALUMINUM D-RING / 45mm

Minimum breaking strength : 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 70g / 2.5oz




S-2667 FORGED SINGLE SLOT ALUMINUM D-RING / 45mm

Minimum breaking strength : 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 81g / 2.8oz




S-2667BT FORGED SINGLE SLOT BENT ALUMINUM D-RING / 45mm

Minimum breaking strength : 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 81g / 2.8oz




S-2388 FORGED SINGLE SLOT ALUMINUM D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 78g / 2.8oz




S-2388BT FORGED SINGLE SLOT BENT ALUMINUM D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 78g / 2.8oz



SINGLE SLOT D-RINGS

(Page 110)


S-2388BT7 FORGED SINGLE SLOT BENT ALUMINUM D-RING / 50mm

Minimum breaking strength : 30kN / 6744LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 78g / 2.8oz




S-2065 SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 134g / 4.7oz




S-916 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 149g / 5.3oz




S-2065-1 SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 133g / 4.7oz




S-2065-1I SINGLE SLOT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 132g / 4.7oz




S-2065-1I6 SINGLE SLOT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 136g / 4.7oz



SINGLE SLOT D-RINGS

(Page 111)


S-2888 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 131g / 4.6oz




S-2888I4 FORGED SINGLE SLOT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 136g / 4.7oz




S-2888I6 FORGED SINGLE SLOT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 136g / 4.7oz




S-2888BT FORGED SINGLE SLOT BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 131g / 4.6oz




S-2888I4BT FORGED SINGLE SLOT BENT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 136g / 4.7oz




S-2888I6BT FORGED SINGLE SLOT BENT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 136g / 4.7oz



SINGLE SLOT D-RINGS

(Page 112)


S-2308 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 114g / 4.0oz




S-2148 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 114g / 4.0oz




S-2277 SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 144g / 5.1oz




S-2331 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 173g / 6.1oz




S-563 FORGED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 243g / 8.6oz




S-2270 FORGED SINGLE SLOT ALUMINUM D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 87g / 3.1oz



SINGLE SLOT D-RINGS

(Page 113)


S-2320 SINGLE SLOT STEEL D-RING WITH TANG / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 127g / 4.5oz




S-2320BT SINGLE SLOT BENT STEEL D-RING WITH TANG / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 127g / 4.5oz




S-2019 FORGED SINGLE SLOT ALUMINUM D-RING / 75mm

Minimum breaking strength : 25kN / 5620LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 107g / 3.8oz




S-2051BT FORGED SINGLE SLOT BENT STEEL D-RING / 65mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 241g / 8.5oz




S-2305 FORGED SINGLE SLOT STEEL D-RING / 65mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 225g / 9oz



SINGLE SLOT D-RINGS

(Page 114)


S-2317PVC PVC COATED FORGED SINGLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 76g / 2.7oz




S-2117PVC PVC COATED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 86g / 3.0oz




S-2063PVC PVC COATED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Black PVC

Weight : 122g / 4.3oz




S-2063BTPVC PVC COATED SINGLE SLOT BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Black PVC

Weight : 122g / 4.3oz




S-2065PVC PVC COATED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 156g / 5.5oz



SINGLE SLOT D-RINGS / DOUBLE SLOT D-RINGS

(Page 115)


S-2065-1PVC PVC COATED SINGLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 161g / 5.7oz




S-2888P FORGED SINGLE SLOT STEEL D-RING / 50mm PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 146g / 5.2oz




S-2888BTP FORGED SINGLE SLOT BENT STEEL D-RING / 50mm PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 146g / 5.2oz




S-2732 FORGED DOUBLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 125g / 4.4oz




S-2732BT FORGED DOUBLE SLOT BENT STEEL D-RING / 45mm

Minimum breaking strength : 23kN / 5171LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 125g / 4.4oz



DOUBLE SLOT D-RINGS

(Page 116)


S-2326 FORGED DOUBLE SLOT STEEL D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 77g / 2.7oz




S-2890 FORGED DOUBLE SLOT ALUMINUM D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 99g / 3.5oz




S-2890BT FORGED DOUBLE SLOT BENT ALUMINUM D-RING / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 99g / 3.5oz




S-2889 FORGED DOUBLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 166g / 5.9oz




S-2889I FORGED DOUBLE SLOT STAINLESS STEEL D-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 166g / 5.9oz



DOUBLE SLOT D-RINGS

(Page 117)


S-2889I4 FORGED DOUBLE SLOT STAINLESS STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 166g / 5.9oz




S-2889BT FORGED DOUBLE SLOT BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 166g / 5.9oz




S-2889IBT FORGED DOUBLE SLOT STAINLESS STEEL / 50mm BENT D-RING

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 166g / 5.9oz




S-2889I4BT FORGED DOUBLE SLOT STAINLESS STEEL / 50mm BENT D-RING

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 166g / 5.9oz




S-915 FORGED DOUBLE SLOT BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 160g / 5.6oz



DOUBLE SLOT D-RINGS

(Page 118)


S-2386 FORGED DOUBLE SLOT BENT ALUMINUM D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 102g / 3.6oz




S-2361 FORGED DOUBLE SLOT STEEL D-RING / 70mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 173g / 6.1oz




S-2889PVC PVC COATED FORGED DOUBLE SLOT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 191g / 6.7oz




S-2889BTPVC PVC COATED FORGED DOUBLE SLOT BENT STEEL D-RING / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Black PVC

Weight : 196g / 6.9oz




S-2889P FORGED DOUBLE SLOT STEEL D-RING / 50mm PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 183g / 6.5oz



DOUBLE SLOT D-RINGS

(Page 119)


S-2889BTP FORGED DOUBLE SLOT BENT STEEL D-RING / 50mm **PLASTIC OVERMOLDED**

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 183g / 6.5oz



BUCKLES

(Page 120)


S-3371A FORGED QUICK CONNECT BUCKLE / 50mm (PATENTED)

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 109g / 3.8oz




S-3371 FORGED QUICK CONNECT BUCKLE / 50mm (PATENTED)

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 111g / 3.9oz




S-3368 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 159g / 5.6oz



S-3369A FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)


Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 98g / 3.5oz

Not available in North America and certain countries



S-3369 FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)


Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 97g / 3.4oz

Not available in North America and certain countries




S-3399A FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 75g / 2.6oz



BUCKLES

(Page 121)


S-3399 FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 74g / 2.6oz




S-3370A FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 95g / 3.4oz




S-3370 FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 95g / 3.4oz




S-3373A FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 114g / 4.0oz




S-3373 FORGED QUICK CONNECT BUCKLE / 45mm (PATENTED)

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 114g / 4.0oz



S-2206 FORGED QUICK CONNECT BUCKLE / 45mm


Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy / High tensile steel

Standard finish (Aluminum alloy) : Anodized

Standard finish (High tensile steel) : Yellow / Silver zinc plate
Chrome plate

Weight : 157g / 5.5oz



BUCKLES

(Page 122)

S-2207 FORGED QUICK CONNECT BUCKLE / 45mm


Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy / High tensile steel

Standard finish (Aluminum alloy) : Anodized

Standard finish (High tensile steel) : Yellow / Silver zinc plate
Chrome plate

Weight : 137g / 4.8oz



S-2207S FORGED QUICK CONNECT BUCKLE / 45mm


Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy / High tensile steel

Standard finish (Aluminum alloy) : Anodized

Standard finish (High tensile steel) : Yellow / Silver zinc plate
Chrome plate

Weight : 118g / 4.2oz




S-2240 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 120g / 4.2oz




S-2506 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 124g / 4.4oz




S-2240I QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 118g / 4.2oz




S-2096 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 204g / 7.2oz



BUCKLES

(Page 123)


S-2096I QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 206g / 7.3oz



S-2085 FORGED QUICK CONNECT BUCKLE / 45mm / 25mm

Minimum breaking strength : 9kN / 2023LBS


Material : Aluminum alloy / High tensile steel

Standard finish (Aluminum alloy) : Anodized

Standard finish (High tensile steel) : Yellow / Silver zinc plate

Chrome plate

Weight : 99g / 3.5oz




S-3398A FORGED QUICK CONNECT BUCKLE / 38mm (PATENTED)

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 70g / 2.4oz




S-3398 FORGED QUICK CONNECT BUCKLE / 38mm (PATENTED)

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 69g / 2.4oz



S-2085A FORGED QUICK CONNECT BUCKLE / 28mm / 25mm

Minimum breaking strength : 9kN / 2023LBS


Material : Aluminum alloy / High tensile steel

Standard finish (Aluminum alloy) : Anodized

Standard finish (High tensile steel) : Yellow / Silver zinc plate

Chrome plate

Weight : 84g / 3oz



S-2432 FORGED QUICK CONNECT BUCKLE / 28mm

Minimum breaking strength : 17.8kN / 4000LBS


Material : Aluminum alloy / High tensile steel

Standard finish (Aluminum alloy) : Anodized

Standard finish (High tensile steel) : Yellow / Silver zinc plate

Chrome plate

Weight : 125g / 4.4oz



BUCKLES

(Page 124)


S-3397A FORGED QUICK CONNECT BUCKLE / 28mm (PATENTED)

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 55g / 1.9oz




S-3397 FORGED QUICK CONNECT BUCKLE / 28mm (PATENTED)

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 55g / 1.9oz



S-2433S FORGED QUICK CONNECT BUCKLE / 28mm


Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy / High tensile steel

Standard finish (Aluminum alloy) : Anodized

Standard finish (High tensile steel) : Yellow / Silver zinc plate
Chrome plate

Weight : 120g / 4.2oz




S-2615I4 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (4mm thick)

Standard finish : Self colored

Weight : 56g / 2.0oz




S-2616I4 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (4mm thick)

Standard finish : Self colored

Weight : 31g / 1.1oz




S-2615 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (2.5mm thick)

Standard finish : Yellow / Silver zinc plate
Black E-Coat

Weight : 35g / 1.2oz



BUCKLES

(Page 125)


S-2616 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate
Black E-Coat

Weight : 22g / 1oz




S-2852 QUICK CONNECT BUCKLE / 30mm

Minimum breaking strength : 15kN / 3372LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate
Black E-Coat

Weight : 25g / 0.9oz




S-2853 QUICK CONNECT BUCKLE / 30mm

Minimum breaking strength : 15kN / 3372LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate
Black E-Coat

Weight : 14g / 0.5oz



S-2928 QUICK CONNECT BUCKLE / 25mm **NEW!**

Minimum breaking strength : 12kN / 2698LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 13g / 0.5oz




S-2928I4 QUICK CONNECT BUCKLE / 25mm

Minimum breaking strength : 10kN / 2248LBS

Material : Stainless steel 304 (3mm thick)

Standard finish : Self colored

Weight : 14g / 0.5oz




S-2929I4 QUICK CONNECT BUCKLE / 25mm

Minimum breaking strength : 10kN / 2248LBS

Material : Stainless steel 304 (3mm thick)

Standard finish : Self colored

Weight : 14g / 0.5oz




S-2898 QUICK CONNECT BUCKLE / 25mm

Minimum breaking strength : 15kN / 3372LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate
Black E-Coat

Weight : 24g / 0.85oz



BUCKLES

(Page 126)

S-2899 QUICK CONNECT BUCKLE / 25mm


Minimum breaking strength : 15kN / 3372LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 14g / 0.5oz



S-2850 QUICK CONNECT BUCKLE / 20mm


Minimum breaking strength : 15kN / 3372LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 17g / 0.6oz



S-2851 QUICK CONNECT BUCKLE / 20mm


Minimum breaking strength : 12kN / 2698LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 10g / 0.4oz




S-2157 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 28g / 1oz




S-2158 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 29g / 1oz




S-2360 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 27g / 1oz




S-2222 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 49g / 1.7oz



BUCKLES

(Page 127)


S-2257 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 48g / 1.7oz



S-2257I QUICK CONNECT BUCKLE / 45mm


Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2

(3mm thick)

Standard finish : Chrome plate

Weight : 48g / 1.7oz




S-2634 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 30g / 1.1oz




S-2635 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 44g / 1.6oz




S-2748 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 36g / 1.3oz




S-951 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 36g / 1.3oz




S-952 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 46g / 1.6oz



BUCKLES

(Page 128)


S-953 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 48g / 1.7oz




S-951I4 STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (4mm thick)

Standard finish : Self colored

Weight : 37g / 1.3oz




S-952I4 STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (4mm thick)

Standard finish : Self colored

Weight : 49g / 1.7oz




S-953I4 STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (4mm thick)

Standard finish : Self colored

Weight : 51g / 1.8oz




S-2278 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 27g / 1oz




S-2279 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 36g / 1.3oz



BUCKLES

(Page 129)


S-2280 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 37g / 1.3oz




S-967 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 32g / 1.1oz




S-968 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 29g / 1oz




S-967I STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2 (4mm thick)

Standard finish : Chrome plate

Weight : 33g / 1.2oz




S-968I STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2 (4mm thick)

Standard finish : Chrome plate

Weight : 31g / 1.1oz




S-967I6 STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 316 (4mm thick)

Standard finish : Self colored

Weight : 40g / 1.4oz




S-968I6 STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 316 (4mm thick)

Standard finish : Self colored

Weight : 37g / 1.3oz



BUCKLES

(Page 130)


S-2058 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 36g / 1.3oz




S-2064 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 42g / 1.5oz





S-2032 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 38g / 1.3oz




S-2033 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 49g / 1.7oz




S-2034 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 94g / 3.3oz




S-2115 FORGED QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 38g / 1.3oz




S-2116 FORGED QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 54g / 1.9oz



BUCKLES

(Page 131)


S-2362 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 35g / 1.2oz




S-2362I STAINLESS STEEL QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2 (3mm thick)

Standard finish : Chrome plate

Weight : 35g / 1.2oz




S-2275 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 33g / 1.2oz




S-2276 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 29g / 1.0oz




S-2273 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 38g / 1.3oz




S-2418 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 45g / 1.6oz




S-2419 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 35g / 1.2oz



BUCKLES

(Page 132)


S-2420 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 73g / 2.6oz




S-2421 QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 57g / 2.0oz




S-2402 QUICK CONNECT BUCKLE / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 29g / 1.0oz



S-2855 QUICK CONNECT BUCKLE / 50mm


Minimum breaking strength : 9kN / 2023LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 75g / 2.6oz



S-2856 QUICK CONNECT BUCKLE / 50mm


Minimum breaking strength : 9kN / 2023LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 90g / 3.2oz




S-2659 ALUMINUM QUICK CONNECT BUCKLE / 25mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 10g / 0.4oz



BUCKLES

(Page 133)


S-2660 ALUMINUM QUICK CONNECT BUCKLE / 25mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 9g / 0.3oz




S-2227 ALUMINUM QUICK CONNECT BUCKLE / 28mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 11g / 0.4oz




S-2226 ALUMINUM QUICK CONNECT BUCKLE / 28mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 10g / 0.4oz




S-2304 ALUMINUM QUICK CONNECT BUCKLE / 28mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 22g / 0.8oz




S-2384 ALUMINUM QUICK CONNECT BUCKLE / 30mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 11g / 0.4oz




S-2615A ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy (4.2mm thick)

Standard finish : Anodized

Weight : 22g / 0.8oz



BUCKLES

(Page 134)


S-2616A ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy (6mm thick)

Standard finish : Anodized

Weight : 16g / 0.6oz




S-2643 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy (5mm thick)

Standard finish : Anodized

Weight : 17g / 0.6oz



ANSI Z359.12
CSA Z259.12


S-2644 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy (5mm thick)

Standard finish : Anodized

Weight : 13g / 0.5oz



ANSI Z359.12
CSA Z259.12


S-2626 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 19g / 0.7oz



ANSI Z359.12
CSA Z259.12


S-2627 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 16g / 0.6oz



ANSI Z359.12
CSA Z259.12


S-2628 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 32g / 1.1oz




ANSI Z359.12
CSA Z259.12

BUCKLES

(Page 135)


S-2224 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 9kN / 2023LBS
Material : Aluminum alloy (4mm thick)
Standard finish : Anodized
Weight : 14g / 0.5oz




S-2228 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 9kN / 2023LBS
Material : Aluminum alloy (4mm thick)
Standard finish : Anodized
Weight : 20g / 0.7oz




S-2225 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 9kN / 2023LBS
Material : Aluminum alloy (4mm thick)
Standard finish : Anodized
Weight : 14g / 0.5oz




S-2426 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 9kN / 2023LBS
Material : Aluminum alloy (4mm thick)
Standard finish : Anodized
Weight : 14g / 0.5oz




S-2425 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 9kN / 2023LBS
Material : Aluminum alloy (4mm thick)
Standard finish : Anodized
Weight : 14g / 0.5oz




S-2292 ALUMINUM QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 9kN / 2023LBS
Material : Aluminum alloy (4mm thick)
Standard finish : Anodized
Weight : 27g / 1oz



S-2058PVC PVC COATED QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS
Material : High tensile steel (4mm thick)
Standard finish : Black PVC
Weight : 38g / 1.3oz



BUCKLES

(Page 136)


S-2402PVC PVC COATED QUICK CONNECT BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Black PVC

Weight : 38g / 1.3oz




S-2607P QUICK CONNECT BUCKLE / 45mm PLASTIC OVERMOLDED

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 39g / 1.4oz




S-2608P QUICK CONNECT BUCKLE / 45mm PLASTIC OVERMOLDED

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 36g / 1.3oz




S-2609P QUICK CONNECT BUCKLE / 45mm PLASTIC OVERMOLDED

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 32g / 1.1oz




S-2606P QUICK CONNECT BUCKLE / 45mm PLASTIC OVERMOLDED

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate overmolded with colored plastic

Weight : 64g / 2.3oz




BUCKLES

(Page 137)

S-2407 PVC PROTECTION SLEEVE

Material : PVC

Weight : 63g / 2.2oz




S-2927I4 STAINLESS STEEL ADJUSTER BUCKLE / 25mm

Minimum breaking strength : 7kN / 1573LBS

Material : Stainless steel 304 (2mm thick)

Standard finish : Self colored

Weight : 15g / 0.5oz




S-936R ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 81g / 2.9oz




S-937R ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 86g / 3oz




S-936RI4 STAINLESS STEEL ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (3.5mm thick)

Standard finish : Self colored

Weight : 84g / 3oz




S-937RI4 STAINLESS STEEL ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (3.5mm thick)

Standard finish : Self colored

Weight : 85g / 3oz



BUCKLES

(Page 138)


S-936S ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 85g / 3oz




S-937S ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 87g / 3.1oz




S-2353 ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy (6mm thick)

Standard finish : Anodized

Weight : 51g / 1.8oz




S-936SI STAINLESS STEEL ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2
(4mm thick)

Standard finish : Chrome plate

Weight : 81g / 2.9oz




S-937SI STAINLESS STEEL ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2
(4mm thick)

Standard finish : Chrome plate

Weight : 82g / 2.9oz




S-2812S ADJUSTER BUCKLE WITH SPRING / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 100g / 3.5oz



BUCKLES

(Page 139)


S-2097 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 102g / 3.6oz




S-2816 ADJUSTER BUCKLE / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Steel (2.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 95g / 3.4oz




S-2439 FORGED ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 79g / 2.8oz




S-2836 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 25g / 0.9oz




S-2836H ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 34g / 1.2oz




S-2372 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 51g / 1.8oz




BUCKLES

(Page 140)


S-23721 STAINLESS STEEL ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS
Material : High tensile stainless steel 420J2
Standard finish : Yellow / Silver zinc plate
Weight : 51g / 1.8oz




S-2299 FORGED ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 85g / 3oz




S-2298 FORGED ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 93g / 3.3oz




S-2436 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 40g / 1.4oz




S-2436BT ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS
Material : High tensile steel
Standard finish : Yellow / Silver zinc plate
Weight : 40g / 1.4oz



S-2016 ADJUSTER BUCKLE / 50mm

Minimum breaking strength : 9kN / 2063LBS
Material : Steel
Standard finish : Yellow / Silver zinc plate
Weight : 88g / 3.1oz



BUCKLES

(Page 141)


S-2672 ADJUSTER BUCKLE / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 65g / 2.2oz




S-2067 ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 90g / 3.2oz




S-2668 ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 109g / 3.8oz




S-2343 ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy (6mm thick)

Standard finish : Anodized

Weight : 54g / 1.9oz




S-2654 STAINLESS STEEL ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 316 (3.5mm thick)

Standard finish : Self colored

Weight : 121g / 4.3oz




S-2067I STAINLESS STEEL ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2 (3.0mm thick)

Standard finish : Chrome plate

Weight : 89g / 3.1oz



BUCKLES

(Page 142)


S-2283 FORGED ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 131g / 4.6oz



S-2210 ADJUSTER BUCKLE WITH SPRING / 45mm


Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.5mm thick)

Ø11mm knurled bar

Standard finish : Yellow / Silver zinc plate

Weight : 93g / 3.3oz



S-2095 FORGED ADJUSTER BUCKLE / 45mm


Minimum breaking strength : 30kN / 6744LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 143g / 5oz



S-2095S FORGED ADJUSTER BUCKLE WITH SPRING / 45mm


Minimum breaking strength : 30kN / 6744LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 166g / 5.9oz




S-2245 ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 41g / 1.4oz




S-2281 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 63g / 2.2oz



BUCKLES

(Page 143)


S-2281BT ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 63g / 2.2oz




S-2356 ADJUSTER BUCKLE / 14mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 42g / 1.5oz




S-2739 ADJUSTER BUCKLE / 22mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (5.0mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 32g / 1.1oz




S-2921 ALUMINUM ADJUSTER BUCKLE / 25mm

Minimum breaking strength : 9kN / 2063LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 16g / 0.6oz




S-2233 ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 24g / 0.8oz




S-2233I4 ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 9kN / 2023LBS

Material : Stainless steel 304 (3.2mm thick)

Standard finish : Self colored

Weight : 24g / 0.8oz




S-2233BT ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 24g / 0.8oz



BUCKLES

(Page 144)


S-2219 ALUMINUM ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 9kN / 2063LBS

Material : Aluminum alloy (4mm thick)

Standard finish : Anodized

Weight : 14g / 0.5oz




S-971 ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (6mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 44g / 1.6oz




S-971I4 STAINLESS STEEL ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304 (6mm thick)

Standard finish : Self color

Weight : 46g / 1.6oz




S-971PVC PVC COATED ADJUSTER BUCKLE / 27mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (6mm thick)

Standard finish : Black PVC

Weight : 49g / 1.7oz




S-971BT ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (6mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 44g / 1.6oz




S-2312 ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 27g / 1oz



BUCKLES

(Page 145)


S-2217 FORGED ADJUSTER BUCKLE / 30mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 36g / 1.3oz




S-2020 FORGED ADJUSTER BUCKLE / 30mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 57g / 2oz




S-2020-1 FORGED ADJUSTER BUCKLE / 30mm

Minimum breaking strength : 9kN / 2023LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 49g / 1.7oz




S-2435 ADJUSTER BUCKLE / 38mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (6mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 57g / 2.0oz




S-2448 FORGED ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 63g / 2.2oz




S-564 FORGED ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 35kN / 7868LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 136g / 4.8oz




S-2354 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 35g / 1.2oz



BUCKLES

(Page 146)


S-969 ADJUSTER BUCKLE / 50mm

Minimum breaking strength : 25kN / 5620LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 65g / 2.3oz




S-969BT BENT ADJUSTER BUCKLE / 50mm

Minimum breaking strength : 25kN / 5620LBS

Material : High tensile steel (5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 62g / 2.2oz




S-2375 ADJUSTER BUCKLE / 50mm

Minimum breaking strength : 20kN / 4496LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 50g / 1.8oz



S-2440BT ADJUSTER BUCKLE / 50mm


Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Black E-Coat

Weight : 63g / 2.2oz




S-2699P ADJUSTER BUCKLE / 50mm PLASTIC OVERMOLDED

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel / Nylon

Standard finish : Yellow / Silver zinc plate
overmolded with colored plastic

Weight : 77g / 2.7oz




S-2359 FORGED OVAL ADJUSTER / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 49g / 1.7oz




S-2359I6 FORGED OVAL ADJUSTER / 45mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 316

Standard finish : Self colored

Weight : 56g / 2.0oz



BUCKLES

(Page 147)


S-2029 FORGED OVAL ADJUSTER / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 70g / 2.5oz




S-2029I4 FORGED OVAL ADJUSTER / 50mm

Minimum breaking strength : 22kN / 5000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 70g / 2.5oz




S-2059 WELDED OVAL ADJUSTER / 45mm

Minimum breaking strength : 12kN / 2698LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 29g / 1oz




S-2059N WELDED OVAL ADJUSTER / 45mm

Minimum breaking strength : 12kN / 2698LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 30g / 1.1oz




S-2671 ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3.2mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 17g / 0.5oz




S-2671I4 ADJUSTER BUCKLE / 28mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304 (3.2mm thick)

Standard finish : Self colored

Weight : 17g / 0.5oz




S-2263 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (3mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 23g / 0.8oz



BUCKLES

(Page 148)


S-2248 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (6mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 46g / 1.6oz




S-2018 FORGED ADJUSTER BUCKLE / 75mm

Minimum breaking strength : 20kN / 4496LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 46g / 1.6oz




S-2715 BRACKET FOR S-2018 / 75mm

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 57g / 2.0oz




S-2820 CNC ALUMINUM O-RING

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 13g / 0.5oz




S-2295 FORGED STEEL O-RING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Steel

Standard finish : Yellow / Silver zinc plate

Weight : 51g / 1.8oz




S-954A FORGED ALUMINUM O-RING

Minimum breaking strength : 15kN / 3372LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 47g / 1.7oz




S-2637 FORGED TONGUE BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 97g / 3.4oz



BUCKLES

(Page 149)


S-2195 TONGUE BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 74g / 2.6oz




S-2195I STAINLESS STEEL TONGUE BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile stainless steel 420J2

Standard finish : Chrome plate

Weight : 75g / 2.6oz




S-2195I4 STAINLESS STEEL TONGUE BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 75g / 2.6oz




S-931B FORGED TONGUE BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 92g / 3.2oz




S-2376 FORGED TONGUE BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 70g / 2.5oz




S-931 FORGED TONGUE BUCKLE / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 92g / 3.2oz



BUCKLES

(Page 150)


S-293014 FORGED TONGUE BUCKLE / 50mm

Minimum breaking strength : 15kN / 3372LBS

Material : Stainless steel 304

Standard finish : Self colored

Weight : 81g / 2.9oz




S-931A FORGED DOUBLE TONGUE BUCKLE / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 108g / 3.8oz




S-2187 FORGED DOUBLE TONGUE BUCKLE / 75mm

Minimum breaking strength : 25kN / 5620LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 145g / 5.1oz




S-2017 FORGED DOUBLE TONGUE BUCKLE / 75mm

Minimum breaking strength : 20kN / 4496LBS

Material : Aluminum alloy

Standard finish : Self colored / Anodized

Weight : 59g / 2.1oz



S-974 BELT BUCKLE / 50mm


Minimum breaking strength : 10kN / 2248LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Chrome plate

Weight : 144g / 5.1oz



S-974R BELT BUCKLE / 50mm


Minimum breaking strength : 10kN / 2248LBS

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Chrome plate

Weight : 147g / 5.2oz




RACING HARNESS HARDWARES

(Page 151)

S-5008 LAP SAFETY BELT QUICK RELEASE / 40mm


Material : Aluminum alloy / High tensile steel
 Standard finish (Aluminum alloy) : Anodized
 Standard finish (High tensile steel) : Chrome plate
 Weight : 418g / 14.7oz



S-2394 LAP SAFETY BELT QUICK RELEASE / 40mm

Material : Aluminum alloy / High tensile steel
 Standard finish (Aluminum alloy) : Anodized
 Standard finish (High tensile steel) : Yellow / Silver zinc plate
 Black E-Coat


Weight : 435g / 15.4oz



S-2441 LAP SAFETY BELT QUICK RELEASE / 40mm

Material : Aluminum alloy / High tensile steel
 Standard finish (Aluminum alloy) : Anodized
 Standard finish (High tensile steel) : Yellow / Silver zinc plate
 Black E-Coat


Weight : 453g / 16oz



S-2442 LAP SAFETY BELT QUICK RELEASE / 40mm


Material : Aluminum alloy / High tensile steel
 Standard finish (Aluminum alloy) : Anodized
 Standard finish (High tensile steel) : Yellow / Silver zinc plate
 Black E-Coat

Weight : 451g / 15.9oz




S-2173 LAP SAFETY BELT QUICK RELEASE / 45mm

Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 200g / 7.1oz



S-2174 LAP SAFETY BELT LINK / 45mm

Material : High tensile steel
 Standard finish : Yellow / Silver zinc plate
 Weight : 90g / 3.2oz



RACING HARNESS HARDWARES


(Page 152)

S-2174L LAP SAFETY BELT LINK WITH LEATHER / 45mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 102g / 3.6oz




S-2172 LAP SAFETY BELT QUICK RELEASE / 75mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 423g / 14.9oz




S-2171 LAP SAFETY BELT LINK / 75mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 164g / 5.8oz




S-2387 ADJUSTER BUCKLE / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 85g / 3oz




S-2231 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 84g / 3oz




S-2232 ADJUSTER BUCKLE WITH SPRING / 45mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 85g / 3oz



RACING HARNESS HARDWARES

(Page 153)


S-2391 ADJUSTER BUCKLE / 75mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : Aluminum alloy

Standard finish : Anodized

Weight : 109g / 3.9oz




S-2170 ADJUSTER BUCKLE / 75mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 141g / 5oz



S-2170S ADJUSTER BUCKLE WITH SPRING / 75mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4.5mm thick)

Standard finish : Yellow / Silver zinc plate

Weight : 143g / 5oz




S-2175 QUICK CONNECT BUCKLE / 50mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (4.5mm)

Standard finish : Yellow / Silver zinc plate

Weight : 81g / 2.9oz




S-2176 ADJUSTER BUCKLE / 75mm

Minimum breaking strength : 17.8kN / 4000LBS

Material : High tensile steel (5mm)

Standard finish : Yellow / Silver zinc plate

Weight : 92g / 3.2oz



S-2165 CENTER LINK

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 85g / 3oz



RACING HARNESS HARDWARES


(Page 154)

S-2168 CENTER LINK

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 53g / 1.9oz




S-2169 CENTER LINK

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 53g / 1.9oz




S-2166 SAFETY BELT LINK / LEFT

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 68g / 2.4oz




S-2167 SAFETY BELT LINK / RIGHT

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 68g / 2.4oz




S-2178 LINK / 25mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 53g / 1.9oz



RACING HARNESS HARDWARES


(Page 155)

S-2031 LINK / 50mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 88g / 3.1oz




S-2177 ANCHOR PLATE / 45mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 78g / 2.8oz




S-2181 ANCHOR PLATE / 40mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 68g / 2.4oz




S-2180 SNAP-IN / 50mm

Material : High tensile steel

Standard finish : Yellow / Silver zinc plate

Weight : 98g / 3.5oz




PLASTIC COMPONENTS

(Page 156)

S-2663 ROPE THIMBLE / 7mm

Available in any color


Weight : 4g / 0.1oz



S-2611 ROPE THIMBLE / 12mm

Available in any color


Weight : 2g / 0.1oz



S-2023 ROPE THIMBLE / 12mm

Available in any color


Weight : 5g / 0.2oz



S-2087 ROPE THIMBLE / 12mm

Available in any color


Weight : 2g / 0.1oz



S-2397 ROPE THIMBLE / 12mm

Available in any color


Weight : 7g / 0.3oz



S-2696 ROPE THIMBLE / 12mm

Available in any color

Weight : 10g / 0.3oz




PLASTIC COMPONENTS

(Page 157)

S-2242 ROPE THIMBLE / 12mm

Available in any color


Weight : 2g / 0.1oz



S-2673 ROPE THIMBLE / 14mm

Available in any color


Weight : 19g / 0.6oz



S-2453 ROPE THIMBLE / 14mm

Available in any color


Weight : 11g / 0.4oz



S-2454 ROPE THIMBLE / 14.5mm

Available in any color


Weight : 19g / 0.7oz



S-2398 ROPE THIMBLE / 16mm

Available in any color


Weight : 2g / 0.1oz



S-2088 ROPE THIMBLE / 16mm

Available in any color

Weight : 3g / 0.1oz




PLASTIC COMPONENTS

(Page 158)

S-2352 ROPE THIMBLE / 16mm

Available in any color


Weight : 3g / 0.1oz



S-2860 ROPE THIMBLE / 18mm

Available in any color


Weight : 6g / 0.2oz



S-2612 ROPE THIMBLE / 18mm

Available in any color


Weight : 3g / 0.1oz



S-2025 BACK PAD / 45mm

Available in any color


Weight : 54g / 1.9oz



S-2201 BACK PAD / 45mm

Available in any color


Weight : 21g / 0.7oz



S-2052 BACK PAD WITH UV RESISTANCE / 45mm

Available in any color

Weight : 37g / 1.3oz




PLASTIC COMPONENTS

(Page 159)

S-2052A BACK PAD WITH UV RESISTANCE / 45mm

Available in any color


Weight : 22g / 0.8oz



S-2182 BACK PAD / 45mm

Available in any color


Weight : 33g / 1.2oz



S-2284 BACK PAD / 45mm

Available in any color


Weight : 5g / 0.2oz



S-2285 BACK PAD / 45mm

Available in any color


Weight : 29g / 1oz



S-2286 BACK PAD / 45mm

Available in any color


Weight : 18g / 0.6oz



S-2287 BACK PAD / 45mm

Available in any color

Weight : 20g / 0.7oz




PLASTIC COMPONENTS

(Page 160)

S-2288 BACK PAD / 45mm

Available in any color


Weight : 31g / 1.1oz



S-2866 BACK PAD / 45mm

Available in any color


Weight 35g / 1.2oz



S-2907 BACK PAD / 45mm

Available in any color


Weight : 62g / 2.2oz



S-2350 BACK PAD / 45mm

Available in any color


Weight : 49g / 1.7oz



S-2858 BACK PAD / 45mm

Available in any color

Weight : 55g / 1.9oz




PLASTIC COMPONENTS

(Page 161)

S-2351 BACK PAD / 45mm

Available in any color


Weight : 82g / 2.9oz



S-2399 BACK PAD / 50mm

Available in any color


Weight : 19g / 0.7oz



S-2133 SHOULDER PAD / 50mm

Available in any color


Weight : 22g / 0.8oz



S-2417 CHEST PAD WITH JEWEL BOX / 50mm

Available in any color


Weight : 19g / 0.7oz



S-2211 CHEST PAD / 50mm

Available in any color

Weight : 7g / 0.2oz




S-2617 CHEST PAD / 45mm

Available in any color

Weight : 19g / 0.7oz

Not available in North America




PLASTIC COMPONENTS

(Page 162)

S-2053 CHEST PAD / 45mm

Available in any color


Weight : 21g / 0.7oz



S-2054 CHEST PAD / 45mm

Available in any color


Weight : 16g / 0.6oz



S-2132 CHEST PAD / 45mm

Available in any color


Weight : 12g / 0.4oz



S-2183 CHEST PAD / 45mm

Available in any color


Weight : 10g / 0.4oz



S-2184 CHEST PAD / 45mm

Available in any color


Weight : 17g / 0.6oz



S-2186 CHEST PAD / 45mm

Available in any color

Weight : 15g / 0.5oz




PLASTIC COMPONENTS

(Page 163)

S-2241 CHEST PAD / 40mm

Available in any color


Weight : 21g / 0.7oz



S-2872 CHEST PAD / 45mm

Available in any color


Weight : 8g / 0.3oz



S-2621 CHEST PAD / 45mm

Available in any color



Weight : 7g / 0.2oz



S-2185 BELT KEEPER / 25mm

Available in any color


Weight : 5g / 0.2oz



S-2291 BELT KEEPER / 40mm

Available in any color


Weight : 7g / 0.2oz



S-2871 BELT KEEPER / 45mm

Available in any color

Weight : 6g / 0.2oz




PLASTIC COMPONENTS

(Page 164)

S-2908 BELT KEEPER / 45mm

Available in any color


Weight : 3g / 0.1oz



S-2800 BELT KEEPER / 45mm

Available in any color


Weight : 7g / 0.2oz



S-2457 BELT KEEPER / 45mm

Available in any color


Weight : 5g / 0.2oz



S-2202 BELT KEEPER / 45mm

Available in any color


Weight : 4g / 0.1oz



S-2102 BELT KEEPER / 45mm

Available in any color


Weight : 3g / 0.1oz



S-2056 BELT KEEPER / 45mm

Available in any color

Weight : 3g / 0.1oz




PLASTIC COMPONENTS

(Page 165)

S-2027 2 PIECE BELT KEEPER / 45mm

Available in any color


Weight : 5g / 0.2oz



S-2252 BELT KEEPER / 50mm

Available in any color


Weight : 3g / 0.1oz



S-2253 BELT KEEPER / 50mm

Available in any color


Weight : 3g / 0.1oz



S-2101 BELT KEEPER / 50mm

Available in any color


Weight : 7g / 0.2oz



S-2212 BELT KEEPER / 50mm

Available in any color


Weight : 3g / 0.1oz



S-2213 BELT KEEPER / 50mm

Available in any color


Weight : 2g / 0.1oz



S-2880 BELT KEEPER WITH CLIP / 45mm

Available in any color

Weight : 11g / 0.4oz




PLASTIC COMPONENTS

(Page 166)

S-2870 BELT KEEPER WITH CLIP / 45mm

Available in any color

Weight : 13g / 0.5oz




S-2215 BELT KEEPERS WITH CLIP (4 models)

Available in any color

Model	Dimensions (mm)		Weight	
	L1	L2	(g)	(oz)
S-2215-30	33.0	38.0	8	0.3
S-2215-45	46.0	51.0	11	0.4
S-2215-50	51.0	56.0	12	0.4
S-2215-55	56.0	61.0	13	0.5

* S-2215-45, S-2215-50 not shown



S-2215-55




S-2215-30

S-2822 SLIP RESISTANCE SLEEVE / 45mm

Available in black


Weight : 43g / 1.5oz



S-2026 SLEEVE / 45mm

Available in black or blue color

Weight : 14g / 0.5oz



S-2405 QUICK CONNECT BUCKLES

Available in any color

Model	Dimensions (mm)			Weight	
	A	B	C	(g)	(oz)
S-2405-10	14.5	10	27.5	1	0.1
S-2405-16	20.4	16	43.8	5	0.2
S-2405-19	25.5	19	53.0	6	0.2
S-2405-25	31.5	25	68.0	12	0.4



S-2405-10


S-2405-19

S-2405-16

S-2405-25




S-2405-25



S-2400 QUICK CONNECT BUCKLE / 20mm

Available in any color

Weight : 6g / 0.2oz




PLASTIC COMPONENTS

(Page 167)

S-2683 QUICK CONNECT BUCKLE / 25mm

Available in any color


Weight : 14g / 0.4oz



S-2255 QUICK CONNECT BUCKLE / 25mm

Available in any color


Weight : 13g / 0.5oz



S-2409 QUICK CONNECT BUCKLE / 25mm

Available in any color

Weight : 8g / 0.3oz



S-2904 QUICK CONNECT BUCKLE (2 models)

Available in any color


Sizes : 28mm and 45mm

Model	Dimensions (mm)			Weight	
	A	B	C	(g)	(oz)
S-2904-28	34.9	28.5	51.2	7	0.2
S-2904-45	58.5	47	85.7	31	1.1

* S-2904-28 not shown




S-2904-45



S-2136 QUICK CONNECT BUCKLE / 50mm

Available in any color

Weight : 35g / 1.2oz




PLASTIC COMPONENTS

(Page 168)

S-2815 QUICK CONNECT BUCKLE / 50mm

Available in any color

Weight : 32g / 1.1oz



S-2917 ADJUSTER BUCKLES (2 models)

Available in any color


Sizes : 38mm and 45mm

Model	Dimensions (mm)			Weight	
	A	B	C	(g)	(oz)
S-2917-38	50.8	39.2	50.3	15	0.5
S-2917-45	57.5	46.5	57.5	23	0.8

* S-2917-38 not shown



S-2917-45



S-2918 ADJUSTER BUCKLES (2 models)

Available in any color


Sizes : 38mm and 45mm

Model	Dimensions (mm)			Weight	
	A	B	C	(g)	(oz)
S-2918-38	54.7	38	50.2	20	0.7
S-2918-45	57.5	46.5	62.5	24	0.8

* S-2918-38 not shown



S-2918-45



S-2824 ADJUSTER BUCKLES (2 models)

Available in any color


Sizes : 45mm and 50mm

Model	Dimensions (mm)			Weight	
	A	B	C	(g)	(oz)
S-2824-45	54.8	46.0	33.6	4	0.1
S-2824-50	61.4	51.5	37.6	6	0.2

* S-2824-50 not shown



S-2824-45



S-2055 ADJUSTER BUCKLES (2 models)

Available in any color


Sizes : 45mm and 50mm

Model	Dimensions (mm)			Weight	
	A	B	C	(g)	(oz)
S-2055-45	53.5	45.0	33.0	5	0.2
S-2055-50	60.5	51.0	37.5	8	0.3

* S-2055-50 not shown




S-2055-45



S-2882 ADJUSTER BUCKLE / 50mm

Available in any color

Weight : 27g / 1.0oz




PLASTIC COMPONENTS

(Page 169)

S-2254 ADJUSTER BUCKLE / 50mm

Available in any color

Weight : 13g / 0.5oz




S-2869 ADJUSTER BUCKLES [2 models]

Available in any color

Sizes : 20mm and 25mm

Model	Dimensions (mm)			Weight	
	A	B	C	(g)	(oz)
S-2869-20	26	19.8	29.5	2	0.1
S-2869-25	31.4	25.7	32.9	4	0.1


* S-2869-25 not shown



S-2135 ADJUSTER BUCKLE / 25mm

Available in any color


Weight : 5g / 0.2oz



S-2137 ADJUSTER BUCKLE / 25mm

Available in any color


Weight : 7g / 0.2oz



S-2134 ADJUSTER BUCKLE / 50mm

Available in any color


Weight : 5g / 0.2oz



S-2900 WEBEND / 45mm

Available in any color

Weight : 4g / 0.1oz




PLASTIC COMPONENTS

(Page 170)

S-2216 WEBEND / 45mm

Available in any color


Weight : 3g / 0.1oz



S-2412 STRAPHOOK / 30mm

Available in any color

Weight : 3g / 0.1oz



S-2883 TOOL HOLDER


Gate mechanism : Straight gate / Self closing / Non-Locking

Minimum breaking strength : 100kgs

Weight : 40g / 1.4oz

Available in any color


Not available in JAPAN



S-2876 SLING RETAINER

Available in any color



Weight : 3g / 0.1oz



S-2931 D-RING ROLLER / 40mm

Available in any color



Weight : 2g / 0.1oz



S-2728 D-RING ROLLER / 45mm

Available in any color

Weight : 3g / 0.1oz




PLASTIC COMPONENTS / ACCESSORIES

(Page 171)

S-2193 D-RING ROLLER / 50mm

Available in any color


Weight : 3g / 0.1oz



S-2302 D-RING ROLLER / 75mm

Available in any color

Weight : 2g / 0.07oz




S-2648 STAINLESS STEEL GROMMET

Material : Stainless steel 304

Standard finish : Self colored

Weight : 2g / 0.1oz




S-2741 WELDED D-RING / 28mm

Minimum breaking strength : **NOT RATED**

Material : Stainless steel 304

Standard finish : Self colored

Weight : 29g / 1.0oz




S-2707BT DOUBLE SLOT BENT BUCKLE / 10mm

Minimum breaking strength : **NOT RATED**

Material : Stainless steel 304

Standard finish : Self colored

Weight : 3g / 0.1oz




S-2704 ADJUSTER BUCKLE / 45mm

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Black E-Coat

Weight : 4g / 0.1oz



ACCESSORIES

(Page 172)


S-2848 ADJUSTER BUCKLE / 50mm

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Black E-Coat

Weight : 14g / 0.5oz




S-2808 WELDED ADJUSTER BUCKLE / 18mm

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Yellow / Silver zinc plate / Chrome plate

Weight : 11g / 0.4oz




S-2677 WELDED ADJUSTER BUCKLE / 25mm

Minimum breaking strength : **NOT RATED**

Material : Stainless steel 304

Standard finish : Self colored

Weight : 9g / 0.3oz




S-2676 WELDED O-RING

Minimum breaking strength : **NOT RATED**

Material : Stainless steel 304

Standard finish : Self colored

Weight : 5g / 0.1oz




S-2675 ACCESSORY AUTOMATIC QUICK RELEASE BUCKLE

Minimum breaking strength : 250kgs

Material : Stainless steel 304

Standard finish : Self colored

Weight : 36g / 1.2oz



S-2666 ACCESSORY STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : 250kgs

Material : High tensile steel

Standard finish : Black E-Coat

Weight : 27g / 1oz



ACCESSORIES

(Page 173)

S-2424 ACCESSORY STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Zinc alloy

Standard finish : Black E-Coat

Weight : 17g / 0.6oz



S-2886 ACCESSORY STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : 200kgs

Material : High tensile steel

Standard finish : Black E-Coat

Weight : 27g / 1.0oz



S-2832 ACCESSORY STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : High tensile steel

Standard finish : Black E-Coat

Weight : 33g / 1.2oz



S-283214 ACCESSORY STRAP SNAPHOOK


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Stainless steel 304

Standard finish : Self colored

Weight : 31g / 1.1oz



S-2423 ACCESSORY STRAP SNAPHOOK / 25mm


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Black E-Coat

Weight : 27g / 1.0oz



S-2655 ACCESSORY STRAP SNAPHOOK / 30mm


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Black E-Coat

Weight : 29g / 1.0oz



ACCESSORIES

(Page 174)

S-2874 TOOL HOLDER


Gate mechanism : Wire gate / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Aluminum alloy

Standard finish : Anodized

Weight : 81g / 2.9oz



S-2873 ACCESSORY CARABINERS (3 models)

Minimum breaking strength : 10kN


Material : Aluminum alloy

Standard finish : Anodized

Optional captive pin available

Model	Gate mechanism	Weight	
		(g)	(oz)
S-2873S	Screw lock / Manual locking	29	1.0
S-2873	Twist lock / Self locking	32	1.1
S-2873T	Triple lock / Self locking	32	1.1

* S-2873T not shown



S-2849 ACCESSORY SNAPHOOK


Gate mechanism : Spring gate / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Black E-Coat

Weight : 31g / 1.1oz



S-2813S ACCESSORY CARABINER


Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : 4kN

Material : Aluminum alloy

Standard finish : Anodized

Weight : 13g / 0.46oz



S-2813BS ACCESSORY CARABINER


Gate mechanism : Straight gate / Self closing / Non-Locking

Minimum breaking strength : 4kN

Material : Aluminum alloy

Standard finish : Anodized

Weight : 11g / 0.4oz



ACCESSORIES

(Page 175)

S-2895BS ACCESSORY CARABINER


Gate mechanism : Straight gate / Self closing / Non-Locking

Minimum breaking strength : 2.5kN

Material : Aluminum alloy

Standard finish : Anodized

Weight : 12g / 0.4oz



S-2862 ACCESSORY CARABINER


Gate mechanism : Wire gate / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : High tensile steel

Standard finish : Magnesium phosphate

Weight : 22g / 0.8oz



S-2879 ACCESSORY CARABINER


Gate mechanism : Wire gate / Self closing / Non-Locking

Minimum breaking strength : 5kN

Material : Aluminum alloy

Standard finish : Anodized

Weight : 17g / 0.6oz



S-2271 ACCESSORY SWIVEL CARABINER


Gate mechanism : Screw lock / Manual locking

Minimum breaking strength : **NOT RATED**

Material : Zinc alloy

Standard finish : Nickel plate

Weight : 26g / 0.92oz



S-2444 ACCESSORY SWIVEL CARABINER


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Zinc alloy

Standard finish : Black E-Coat

Weight : 15g / 0.6oz



ACCESSORIES

(Page 176)

S-2445 ACCESSORY SWIVEL CARABINER


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Zinc alloy

Standard finish : Black E-Coat

Weight : 38g / 1.4oz



S-2446 ACCESSORY SWIVEL CARABINER


Gate mechanism : Single action / Self closing / Non-Locking

Minimum breaking strength : **NOT RATED**

Material : Zinc alloy

Standard finish : Black E-Coat

Weight : 35g / 1.3oz




S-2934 ACCESSORY SWIVEL CARABINER **NEW!**

Minimum breaking strength : **NOT RATED**

Material : Zinc alloy

Standard finish : Black E-Coat

Weight : 35g / 1.2oz




S-2887 BUMP STRAP BUCKLE / 25mm

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Black E-Coat

Weight : 13g / 0.5oz




S-2887I4 BUMP STRAP BUCKLE / 25mm

Minimum breaking strength : **NOT RATED**

Material : Stainless steel 304

Standard finish : Self colored / Black E-Coat

Weight : 13g / 0.5oz




S-2422 BUMP STRAP BUCKLE / 25mm

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Black E-Coat

Weight : 12g / 0.4oz




S-2601 BUMP STRAP BUCKLE / 25mm

Minimum breaking strength : 350kgs

Material : High tensile steel

Standard finish : Black E-Coat

Weight : 17g / 0.6oz




S-2915 BUMP STRAP BUCKLE / 40mm

Minimum breaking strength : 100kgs

Material : High tensile steel

Standard finish : Black E-Coat

Weight : 29g / 1.0oz




S-2916 BUMP STRAP BUCKLE / 40mm

Minimum breaking strength : 100kgs

Material : High tensile steel

Standard finish : Black E-Coat

Weight : 29g / 1.0oz




S-2658 ADJUSTER BUCKLE / 27mm

Minimum breaking strength : **NOT RATED**

Material : Stainless steel 304

Standard finish : Self colored

Weight : 11g / 0.4oz



ACCESSORIES

(Page 178)


S-2346 ACCESSORY NUTS (2 models)

Minimum breaking strength : **NOT RATED**

Material : Aluminum alloy

Standard finish : Anodized

Model	Dimensions (mm)		Weight	
	L	W	(g)	(oz)
S-2346S	48	8	1	0.05
S-2346L	55	10	2	0.07




S-2414 STEEL LOCKOUT

Minimum breaking strength : **NOT RATED**

Material : Steel

Standard finish : Lacquer coating



Weight : 117g / 4.1oz



S-2614 NUT TOOLS (2 models)

Model	Material	Standard finish	Weight	
			(g)	(oz)
S-2614	High tensile steel	Yellow / Silver zinc plate	76	2.7
S-2614I	High tensile stainless steel 420J2	Self colored	74	2.6

* S-2614 not shown



INDEX

Model ref.	Page no.				
6636-7	76	S-2011I	51	S-2036L	89
6636I6-7	76	S-2011IS	51	S-2037I	89
689P10	69	S-2011IT	51	S-2037IL	89
7350-10	78	S-2011K	53	S-2038	89
7350-8	77	S-2011KO	53	S-2038-1	89
7350I6-10	78	S-2011KOS	53	S-2038-1I	89
7350I6-8	77	S-2011KOT	53	S-2038-1L	89
7352-8	77	S-2011KS	53	S-2038I	89
7352I6-8	77	S-2011KT	53	S-2038IL	89
7360-10	78	S-2011O	52	S-2038L	89
7360-8	77	S-2011OS	52	S-2039	87
7360I6-10	78	S-2011OT	52	S-2042-100	28
7360I6-8	77	S-2011S	51	S-2042-50	28
S-2001	23	S-2011T	51	S-2042-75	28
S-2002	57	S-2012	75	S-2043	30
S-2002BS	57	S-2012T	75	S-2046	9
S-2002S	57	S-2016	140	S-2049	11
S-2002T	57	S-2017	150	S-2050I	29
S-2003	73	S-2018	148	S-2050IL	29
S-2004	63	S-2019	113	S-2050L	29
S-2004K	63	S-2020	145	S-2051BT	113
S-2004KS	63	S-2020-1	145	S-2052	158
S-2004KT	63	S-2022	102	S-2052A	159
S-2004S	63	S-2023	156	S-2053	162
S-2004T	63	S-2025	158	S-2054	162
S-2005	27	S-2026	166	S-2055-45	168
S-2008	10	S-2027	165	S-2055-50	168
S-2008-1	11	S-2028	103	S-2056	164
S-2008-1I	11	S-2029	147	S-2057	103
S-2008C	18	S-2029I4	147	S-2058	130
S-2009	75	S-2031	155	S-2058PVC	135
S-2010	66	S-2032	130	S-2059	147
S-2010I	66	S-2033	130	S-2059N	147
S-2010IS	66	S-2034	130	S-2063	107
S-2010IT	66	S-2035	88	S-2063BT	107
S-2010K	66	S-2035I	88	S-2063BTPVC	114
S-2010KS	66	S-2035IL	88	S-2063PVC	114
S-2010KT	66	S-2035L	88	S-2064	130
S-2010S	66	S-2036	89	S-2065	110
S-2010T	66	S-2036I	89	S-2065-1	110
S-2011	51	S-2036IL	89	S-2065-1I	110
				S-2065-1I6	110
				S-2065-1PVC	115
				S-2065PVC	114
				S-2067	141
				S-2067I	141
				S-2071	71
				S-2071A	71
				S-2071AS	71
				S-2071AT	71
				S-2071IS	70
				S-2071K	72
				S-2071KS	72
				S-2071KT	72
				S-2071S	71
				S-2071T	71
				S-2074I	90
				S-2078	24
				S-2078M	24
				S-2078W	24
				S-2079	70
				S-2081	64
				S-2081S	64
				S-2081T	64
				S-2083	44
				S-2083A	44
				S-2084	27
				S-2084A	27
				S-2084P	28
				S-2085	123
				S-2085A	123
				S-2086	35
				S-2087	156
				S-2088	157
				S-2089	10
				S-2090	13
				S-2090-1	13
				S-2090-1A	13
				S-2090-1AK	13
				S-2090-1K	13
				S-2091	79
				S-2091A	79

INDEX

Model ref.	Page no.				
S-2092	80	S-2117PVC	114	S-2150	36
S-2093	22	S-2122	95	S-2150A	37
S-2095	142	S-2122C	95	S-2150AL	37
S-2095S	142	S-2122CB	95	S-2150AS	37
S-2096	122	S-2124	79	S-2150ASL	37
S-2096I	123	S-2124C	80	S-2150AT	37
S-2097	139	S-2124I	80	S-2150ATL	37
S-2100	101	S-2126	38	S-2150C	37
S-2101	165	S-2126-1	39	S-2150CI	37
S-2102	164	S-2126-1I	39	S-2150CIT	37
S-2104	100	S-2126-1L	39	S-2150CT	37
S-2107	58	S-2126-2	38	S-2150I	36
S-2107A	59	S-2126-2L	38	S-2150IL	36
S-2107AK	59	S-2126B	38	S-2150IT	36
S-2107AKS	59	S-2126H	38	S-2150ITL	36
S-2107AKT	59	S-2126HB	38	S-2150L	36
S-2107AS	59	S-2127	93	S-2150T	36
S-2107AT	59	S-2128	94	S-2150TL	36
S-2107K	59	S-2129	95	S-2151	74
S-2107KS	59	S-2129CB	95	S-2151A	74
S-2107KT	59	S-2130	96	S-2151T	74
S-2107S	58	S-2132	162	S-2152	11
S-2107T	58	S-2133	161	S-2153	98
S-2109ABB	50	S-2134	169	S-2156	12
S-2109ABS	50	S-2135	169	S-2156A	12
S-2109AS	50	S-2136	167	S-2157	126
S-2109AWB	50	S-2137	169	S-2158	126
S-2109AWS	50	S-2142	96	S-2162	99
S-2109KBB	50	S-2146	30	S-2165	153
S-2109WB	50	S-2146A	29	S-2166	154
S-2109WS	50	S-2148	112	S-2167	154
S-2111	70	S-2149	41	S-2168	154
S-2111A	70	S-2149A	43	S-2169	154
S-2112	23	S-2149AS	43	S-2170	153
S-2113E	74	S-2149AT	43	S-2170S	153
S-2115	130	S-2149K	42	S-2171	152
S-2116	130	S-2149KS	42	S-2172	152
S-2117	106	S-2149KT	42	S-2173	151
S-2117BT	106	S-2149O	41	S-2174	151
S-2117I4	106	S-2149OT	41	S-2174L	152
S-2117I4BT	106	S-2149T	41	S-2175	153
				S-2176	153
				S-2177	155
				S-2178	154
				S-2180	155
				S-2181	155
				S-2182	159
				S-2183	162
				S-2184	162
				S-2185	163
				S-2186	162
				S-2187	150
				S-2188	73
				S-2189O	73
				S-2190O	76
				S-2191	89
				S-2191I	89
				S-2191IL	89
				S-2191L	89
				S-2192	106
				S-2193	171
				S-2194AWB	68
				S-2195	149
				S-2195I	149
				S-2195I4	149
				S-2196O	65
				S-2196OBS	65
				S-2196OS	65
				S-2196OT	65
				S-2197K	67
				S-2197KS	67
				S-2197KT	67
				S-2197O	67
				S-2197OS	67
				S-2197OT	67
				S-2198K	54
				S-2198KO	55
				S-2198KOS	55
				S-2198KOT	55
				S-2198KS	54
				S-2198KT	54
				S-2199	79

INDEX

Model ref.	Page no.				
S-2200	86	S-2235	76	S-2271	175
S-2200B	86	S-2237	87	S-2272	80
S-2200T	86	S-2237B	87	S-2272A	80
S-2200TB	86	S-2238AWS	48	S-2272I	81
S-2200TS	86	S-2239	14	S-2273	131
S-2201	158	S-2239A	14	S-2275	131
S-2202	164	S-2240	122	S-2276	131
S-2203AWB	49	S-2240I	122	S-2277	112
S-2203AWS	49	S-2241	163	S-2278	128
S-2206	121	S-2242	157	S-2279	128
S-2207	122	S-2243	97	S-2280	129
S-2207S	122	S-2245	142	S-2281	142
S-2208	81	S-2246	102	S-2281BT	143
S-2208I	81	S-2247ABB	49	S-2282	82
S-2210	142	S-2247ABS	49	S-2283	142
S-2211	161	S-2247AS	49	S-2284	159
S-2212	165	S-2247BB	49	S-2285	159
S-2213	165	S-2248	148	S-2286	159
S-2215-30	166	S-2249A	47	S-2287	159
S-2215-45	166	S-2249ABS	47	S-2288	160
S-2215-50	166	S-2249AS	47	S-2289	101
S-2215-55	166	S-2249AT	47	S-2289I	101
S-2216	170	S-2250	10	S-2290	64
S-2217	145	S-2251	91	S-2290A	64
S-2219	144	S-2252	165	S-2290AS	64
S-2222	126	S-2253	165	S-2290AT	64
S-2224	135	S-2254	169	S-2290S	64
S-2225	135	S-2255	167	S-2290T	64
S-2226	133	S-2257	127	S-2291	163
S-2227	133	S-2257I	127	S-2292	135
S-2228	135	S-2259	87	S-2295	148
S-2229	21	S-2260	88	S-2295H	97
S-2230	23	S-2261	97	S-2298	140
S-2231	152	S-2261I6	97	S-2299	140
S-2232	152	S-2262	102	S-2300ABB	50
S-2233	143	S-2263	147	S-2300ABS	50
S-2233BT	143	S-2265	106	S-2300AS	50
S-2233I4	143	S-2265I4	107	S-2302	171
S-2234	105	S-2267	82	S-2303	9
S-2234BT	105	S-2269	81	S-2304	133
S-2234I	105	S-2270	112	S-2305	113
				S-2306	98
				S-2307	107
				S-2308	112
				S-2309	82
				S-2309S	82
				S-2310	60
				S-2310A	61
				S-2310ABS	61
				S-2310AS	61
				S-2310AT	61
				S-2310I6	60
				S-2310I6S	60
				S-2310I6T	60
				S-2310S	60
				S-2310T	60
				S-2311	99
				S-2312	144
				S-2313	82
				S-2314-10	93
				S-2314-12	93
				S-2314-8	93
				S-2314I-10	93
				S-2314I-12	93
				S-2315AWB	49
				S-2315AWS	49
				S-2316	83
				S-2317	105
				S-2317PVC	114
				S-2318	91
				S-2319A	65
				S-2319AS	65
				S-2319AT	65
				S-2320	113
				S-2320BT	113
				S-2324	83
				S-2326	116
				S-2327	20
				S-2327I	21
				S-2328	21
				S-2329	21
				S-2331	112

INDEX

Model ref.	Page no.				
S-2332	108	S-2364IT	44	S-2413	99
S-2332BT	108	S-2364S	43	S-2414	178
S-2332BT7	109	S-2364T	43	S-2416	53
S-2333	38	S-2372	139	S-2416K	54
S-2333B	38	S-2372I	140	S-2416KS	54
S-2335A	30	S-2375	146	S-2416KT	54
S-2335AL	30	S-2376	149	S-2416S	53
S-2336	92	S-2379	9	S-2416T	53
S-2339	108	S-2381	90	S-2417	161
S-2339BT	108	S-2382IL	90	S-2418	131
S-2340	19	S-2383	20	S-2419	131
S-2343	141	S-2384	133	S-2420	132
S-2344I6-M16	92	S-2386	118	S-2421	132
S-2344-M13	92	S-2387	152	S-2422	177
S-2344-M16	92	S-2388	109	S-2423	173
S-2344-M19	92	S-2388BT	109	S-2424	173
S-2345A	48	S-2388BT7	110	S-2425	135
S-2345ABS	48	S-2389A	51	S-2426	135
S-2345AS	48	S-2389AS	51	S-2431	81
S-2345AT	48	S-2389AT	51	S-2432	123
S-2346L	178	S-2390	19	S-2433S	124
S-2346S	178	S-2391	153	S-2435	145
S-2350	160	S-2393	11	S-2436	140
S-2351	161	S-2394	151	S-2436BT	140
S-2352	158	S-2396	104	S-2437K	42
S-2353	138	S-2396BT	104	S-2437KS	42
S-2354	145	S-2397	156	S-2437KT	42
S-2356	143	S-2398	157	S-2439	139
S-2358	39	S-2399	161	S-2440BT	146
S-2359	146	S-2400	166	S-2441	151
S-2359I6	146	S-2402	132	S-2442	151
S-2360	126	S-2402PVC	136	S-2444	175
S-2361	118	S-2403I-10	93	S-2445	176
S-2362	131	S-2403I-12	93	S-2446	176
S-2362I	131	S-2405-10	166	S-2448	145
S-2364	43	S-2405-16	166	S-2450	45
S-2364A	44	S-2405-19	166	S-2451	41
S-2364AS	44	S-2405-25	166	S-2452	52
S-2364AT	44	S-2407	137	S-2452BS	52
S-2364I	44	S-2409	167	S-2452S	52
S-2364IS	44	S-2412	170	S-2452T	52
				S-2453	157
				S-2454	157
				S-2457	164
				S-2500	25
				S-2500T	25
				S-2500TAZ NEW!	25
				S-2506	122
				S-2601	177
				S-2602	102
				S-2602BT	102
				S-2605	94
				S-2606P	136
				S-2607P	136
				S-2608P	136
				S-2609P	136
				S-2611	156
				S-2612	158
				S-2613	27
				S-2614	178
				S-2614I	178
				S-2615	124
				S-2615A	133
				S-2615I4	124
				S-2616	125
				S-2616A	134
				S-2616I4	124
				S-2617	161
				S-2618	88
				S-2618H	88
				S-2619	41
				S-2619S	41
				S-2619T	41
				S-2620	93
				S-2621	163
				S-2623	94
				S-2625	8
				S-2625A	8
				S-2626	134
				S-2627	134
				S-2628	134
				S-2629A	58

INDEX

Model ref.	Page no.				
S-2629AS	58	S-2671I4	147	S-2713T	69
S-2629AT	58	S-2672	141	S-2715	148
S-2630	98	S-2673	157	S-2716	38
S-2632	8	S-2675	172	S-2721	88
S-2632A	8	S-2676	172	S-2723	44
S-2633I	47	S-2677	172	S-2723S	44
S-2633IS	47	S-2679	35	S-2723T	44
S-2633IT	47	S-2679L	35	S-2727	22
S-2634	127	S-2679S	35	S-2728	170
S-2635	127	S-2679SL	35	S-2732	115
S-2635	127	S-2679T	35	S-2732BT	115
S-2637	148	S-2679TL	35	S-2733	87
S-2638A	62	S-2680	100	S-2734T	69
S-2638AS	62	S-2680P	101	S-2738	85
S-2638AT	62	S-2681	98	S-2739	143
S-2639	91	S-2681P	98	S-2741	171
S-2640	79	S-2682	14	S-2742	101
S-2641	94	S-2682A	14	S-2742BT	101
S-2642	94	S-2683	167	S-2745	47
S-2643	134	S-2690S	62	S-2745S	47
S-2644	134	S-2692	86	S-2745T	47
S-2645	10	S-2692B	86	S-2746	95
S-2647A	48	S-2696	156	S-2748	127
S-2647ABS	48	S-2697IS	61	S-2755	68
S-2647AS	48	S-2699P	146	S-2800	164
S-2647AT	48	S-2700	45	S-2801	45
S-2648	171	S-2700BS	45	S-2803	58
S-2653	12	S-2700S	45	S-2803S	58
S-2654	141	S-2700T	45	S-2803T	58
S-2655	173	S-2701	39	S-2804	68
S-2657BTP	105	S-2704	171	S-2804S	68
S-2657P	105	S-2706	95	S-2804T	68
S-2658	177	S-2707BT	171	S-2805S	68
S-2659	132	S-2709	85	S-2808	172
S-2660	133	S-2710	34	S-2812S	138
S-2663	156	S-2710L	34	S-2813BS	174
S-2666	172	S-2711O	47	S-2813S	174
S-2667	109	S-2711OS	47	S-2815	168
S-2667BT	109	S-2711OT	47	S-2816	139
S-2668	141	S-2712	74	S-2819	61
S-2671	147	S-2713	69	S-2819S	61
				S-2819T	61
				S-2820	148
				S-2821	104
				S-2822	166
				S-2824-45	168
				S-2824-50	168
				S-2826	99
				S-2828	99
				S-2830	22
				S-2832	173
				S-2832I4	173
				S-2834	99
				S-2835	87
				S-2836	139
				S-2836H	139
				S-2840	99
				S-2847	102
				S-2848	172
				S-2849	174
				S-2850	126
				S-2851	126
				S-2852	125
				S-2853	125
				S-2854	22
				S-2855	132
				S-2856	132
				S-2857	99
				S-2858	160
				S-2860	158
				S-2862	175
				S-2863	40
				S-2866	160
				S-2869-20	169
				S-2869-25	169
				S-2870	166
				S-2871	163
				S-2872	163
				S-2873	174
				S-2873S	174
				S-2873T	174
				S-2874	174

INDEX

Model ref.	Page no.				
S-2875	107	S-2908	164	S-3397A	124
S-2875BT	107	S-2910	49	S-3398	123
S-2876	170	S-2910S	49	S-3398A	123
S-2877	40	S-2910T	49	S-3399	121
S-2879	175	S-2915	177	S-3399A	120
S-2880	165	S-2916	177	S-3602	16
S-2882	168	S-2917-38	168	S-3603	16
S-2883	170	S-2917-45	168	S-3605	31
S-2886	173	S-2918-38	168	S-3605L	31
S-2887	176	S-2918-45	168	S-3606	17
S-2887I4	176	S-2921	143	S-3607	17
S-2888	111	S-2923	86	S-3608	17
S-2888BT	111	S-2924	85	S-3609	17
S-2888BTP	115	S-2925	23	S-3610	17
S-2888I4	111	S-2926	33	S-3611	18
S-2888I4BT	111	S-2926L	34	S-3612	26
S-2888I6	111	S-2927I4	137	S-3614	16
S-2888I6BT	111	S-2928 NEW!	125	S-3615	26
S-2888P	115	S-2928I4	125	S-3616	34
S-2889	116	S-2929I4	125	S-3616L	35
S-2889BT	117	S-2930I4	150	S-3617	33
S-2889BTP	119	S-2931	170	S-3617L	33
S-2889BT-PVC	118	S-2933	99	S-3618	26
S-2889I	116	S-2934 NEW!	176	S-3619	32
S-2889I4	117	S-2935S	72	S-3619L	32
S-2889I4BT	117	S-2940 NEW!	14	S-3620	18
S-2889IBT	117	S-2940N NEW!	15	S36-2003	73
S-2889P	118	S-302	9	S36-2009	75
S-2889PVC	118	S-302I	9	S36-2009T	76
S-2890	116	S-302L	8	S36-2012	75
S-2890BT	116	S-334	18	S36-2071	71
S-2892	22	S-3368	120	S36-2071I	71
S-2893	40	S-3369	120	S36-2071IT	71
S-2895BS	175	S-3369A	120	S36-2071K	72
S-2898	125	S-3370	121	S36-2071KT	72
S-2899	126	S-3370A	121	S36-2071T	71
S-2900	169	S-3371	120	S-3621	31
S-2904-28	167	S-3371A	120	S36-2111	70
S-2904-45	167	S-3373	121	S36-2111I	70
S-2907	160	S-3373A	121	S36-2151	74
		S-3397	124	S36-2188	73
				S36-2189O	73
				S36-2190O	76
				S-3621I	32
				S-3621IL	32
				S-3621L	32
				S-3622	19
				S-3623	19
				S36-2370	43
				S36-2370K	43
				S36-2370KT	43
				S36-2370T	43
				S36-2371	65
				S36-2371K	65
				S36-2371KT	65
				S36-2371T	65
				S-3624	19
				S-3625	33
				S-3625L	33
				S-3626	20
				S36-2646	62
				S36-2646T	62
				S36-2690	63
				S36-2690T	63
				S-3627	20
				S36-2712	75
				S-3628	16
				S36-2806	62
				S36-2806T	62
				S-3629	18
				S36-2935	72
				S36-2935T	72
				S-3631	16
				S-3634	26
				S-3638	15
				S-3639	15
				S-3640	26
				S-3642	31
				S-3642L	31
				S-3651	35
				S-3651L	35
				S-3669	37

INDEX

Model ref.	Page no.						
S-3669L	37	S50-2150T	36	S-507-1KBS	46	S-936RI4	137
S-3669T	37	S50-2150TL	36	S-507-1KS	46	S-936S	138
S-3669TL	37	S50-2197K	67	S-507-1KT	46	S-936SI	138
S-3691	15	S50-2197KT	67	S-507-1T	45	S-937R	137
S-398	12	S50-2197O	67	S50-958	55	S-937RI4	137
S-399	15	S50-2197OT	67	S50-958I	57	S-937S	138
S-5008	151	S50-2198K	54	S50-958IK	56	S-937SI	138
S50-2004	63	S50-2198KO	55	S50-958IKT	56	S-938	108
S50-2004K	64	S50-2198KOT	55	S50-958IT	57	S-938BT	108
S50-2004KT	64	S50-2198KT	54	S50-958K	56	S-951	127
S50-2004T	63	S50-2290	64	S50-958KT	56	S-951I4	128
S50-2010	66	S50-2290T	64	S50-958T	55	S-952	127
S50-2010I	66	S50-2310	60	S-562	103	S-952I4	128
S50-2010IT	66	S50-2310I	60	S-563	112	S-953	128
S50-2010K	67	S50-2310IT	60	S-564	145	S-953I4	128
S50-2010KT	67	S50-2310T	60	S-565	100	S-954	97
S50-2010T	66	S50-2364	43	S-565BT	100	S-954A	148
S50-2011	51	S50-2364T	43	S-565I4	100	S-954I	97
S50-2011K	53	S50-2416K	54	S-565I6	100	S-954I6	98
S50-2011KO	53	S50-2416KT	54	S-565PVC	103	S-954PVC	99
S50-2011KOT	53	S50-2437K	42	S-630	44	S-955	103
S50-2011KT	53	S50-2437KT	42	S-630A	44	S-955BT	104
S50-2011O	52	S50-2679	35	S-630L	44	S-955I	104
S50-2011OT	52	S50-2679L	35	S-633	10	S-955I4	104
S50-2011T	51	S50-2679T	35	S-634	23	S-956AS	48
S50-2107	58	S50-2679TL	35	S-8088CBL	84	S-956AWB	48
S50-2107IK	59	S50-2697I	61	S-8088CBL V2	84	S-956AWS	48
S50-2107IKT	59	S50-2697IT	61	S-8088CL	84	S-958	55
S50-2107K	59	S50-2736I	52	S-8088L	83	S-958A	57
S50-2107KT	59	S50-2736IT	52	S-8088L V2	83	S-958AK	57
S50-2107T	58	S50-2802	41	S-8088R	84	S-958AKS	57
S50-2149	42	S50-2805	68	S-8088R V2	83	S-958AKT	57
S50-2149K	42	S50-2805T	68	S-8088W45L	85	S-958AS	57
S50-2149KT	42	S50-507-1	46	S-8088W45L V2	85	S-958AT	57
S50-2149T	42	S50-507-1K	46	S-839	30	S-958I	57
S50-2150	36	S50-507-1KT	46	S-915	117	S-958IKS	56
S50-2150I	36	S50-507-1T	46	S-916	110	S-958IS	57
S50-2150IL	36	S-507	45	S-931	149	S-958IT	57
S50-2150IT	36	S-507-1	45	S-931A	150	S-958K	56
S50-2150ITL	36	S-507-1BS	45	S-931B	149	S-958KS	56
S50-2150L	36	S-507-1K	46	S-936R	137	S-958KT	56

INDEX

Model ref.	Page no.		
S-958S	55	S-9981A	27
S-958T	55	S-999	12
S-958WB	55	S-9981A	27
S-958WS	55	S-999	12
S-960	91		
S-960-2	91		
S-960-2C	91		
S-960-2S	91		
S-960-2SC	91		
S-960-3	91		
S-960-3C	91		
S-960-3S	91		
S-960-3SC	91		
S-960C	91		
S-960S	91		
S-960SC	91		
S-962AS	46		
S-963	88		
S-963H	88		
S-963L	88		
S-964	103		
S-967	129		
S-967I	129		
S-967I6	129		
S-968	129		
S-968I	129		
S-968I6	129		
S-969	146		
S-969BT	146		
S-970	20		
S-971	144		
S-971BT	144		
S-971I4	144		
S-971PVC	144		
S-974	150		
S-974R	150		
S-979-22	24		
S-979-28	25		
S-979C	24		
S-979P	25		
S-989	21		



USANG INDUSTRIAL CO., LTD.

7F., No.35, Dexing W. Rd.,
Shilin Dist., Taipei 11158,
TAIWAN

Tel: +886-2-28331147

Fax: +886-2-28337826

E-mail: sales@usang.com.tw

Web: www.usang.com.tw

